

Axial Lead and Cartridge Fuses

Midget

Laminated Body Fast-Acting Type BLF Series




ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
135%	1 hour, Maximum
200%	2 minutes, Maximum

AGENCY APPROVALS: Listed by Underwriters Laboratories and Certified by CSA.

INTERRUPTING RATING: 10,000 amperes at rated VAC.

NOTE: Not recommended for applications in humid areas.



ORDERING INFORMATION:

Cartridge Catalog Number	Ampere Rating	AC Voltage Rating	Nominal Resistance Cold Ohms
BLF .500	.500	250	1.57
BLF 001.	1	250	.395
BLF 1.5	1.5	250	.2191
BLF 002.	2	250	.125
BLF 2.5	2.5	250	.0946
BLF 003.	3	250	.0696
BLF 004.	4	250	.0432
BLF 005.	5	250	.0413
BLF 006.	6	260	.02842
BLF 6.25	6.25	250	.02741
BLF 007.	7	250	.02282
BLF 008.	8	250	.01664
BLF 009.	9	250	.01364
BLF 010.	10	250	.01097
BLF 012.	12	250	.00920
BLF 015.	15	250	.00684
BLF 020.	20	125	.00528
BLF 025.	25	125	.00378
BLF 030.	30	125	.00289

RoHS Fibre Body Fast-Acting Type BLN Series




ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
135%	1 hour, Maximum
200%	2 minutes, Maximum

AGENCY APPROVALS: Listed by Underwriters Laboratories and Certified by CSA.

INTERRUPTING RATING: 10,000 amperes at 250 VAC.

FUSES TO MIL SPEC: See F09A type in Military Section.



ORDERING INFORMATION:

Cartridge Catalog Number	Ampere Rating	AC Voltage Rating	Nominal Resistance Cold Ohms
BLN 1	1	250	.395
BLN 1 1/2	1.5	250	.222
BLN 2*	2	250	.125
BLN 3	3	250	.071
BLN 4	4	250	.0432
BLN 5	5	250	.0413
BLN 6	6	250	.0284
BLN 8	8	250	.0166
BLN 10	10	250	.011
BLN 12	12	250	.00920
BLN 15	15	250	.00684
BLN 20	20	250	.0036
BLN 25	25	250	.00270
BLN 30	30	250	.00230

* 2 A device not lead-free or RoHS compliant

11
AXIAL LEAD AND CARTRIDGE FUSES
11
AXIAL LEAD AND CARTRIDGE FUSES