


VOLTAGE RANGE: 1000 - 1800V
CURRENT: 1.0 A

Features

- Fast switching
- Diffused junction
- Low leakage
- Low forward voltage drop
- High current capability
- Easily cleaned with alcohol, Isopropanol and similar solvents

Mechanical Data

- Case: JEDEC R--1, molded plastic
- Polarity: Color band denotes cathode
- Weight: 0.007 ounces, 0.20 grams
- Mounting position: Any



Dimensions in millimeters




Maximum Ratings and Electrical Characteristics T_A = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

| Characteristic | Symbol | 1A10F | 1A12F | 1A14F | 1A15F | 1A16F | 1A18F | UNITS |
|---|--------------------|----------------|-------|-------|-------|-------|-------|-------|
| Maximum recurrent peak reverse voltage | V _{RRM} | 1000 | 1200 | 1400 | 1500 | 1600 | 1800 | V |
| Maximum RMS voltage | V _{RMS} | 700 | 840 | 980 | 1050 | 1120 | 1260 | V |
| Maximum DC blocking voltage | V _{DC} | 1000 | 1200 | 1400 | 1500 | 1600 | 1800 | V |
| Maximum average forward rectified current 9.5mm lead length, @T _A =75°C | I _{F(AV)} | 1.0 | | | | | | A |
| Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load T _J =125°C | I _{FSM} | 30.0 | | | | | | A |
| Maximum instantaneous forward voltage @ 1.0 A | V _F | 1.3 | | | 1.8 | | | V |
| Maximum reverse current @T _A =25°C at rated DC blocking voltage @T _A =100°C | I _R | 5.0 100.0 | | | | | | μA |
| Maximum reverse recovery time (NOTE1) | t _{rr} | 300 | | | | | | ns |
| Typical junction capacitance (NOTE2) | C _J | 15 | | | | | | pF |
| Operating junction temperature range | T _J | -55 ---- + 150 | | | | | | °C |
| Storage temperature range | T _{STG} | -55 ---- + 150 | | | | | | °C |

NOTE: 1. Reverse recovery test conditions: I_F=0.5A, I_R=1.0A, I_{RR}=0.25A.

2. Measured at 1MHz and applied reverse voltage of 4.0V.

FIG.1 – FORWARD DERATING CURVE

FIG.2 – PEAK FORWARD SURGE CURRENT

FIG.3 – TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC


NOTES: 1. RISE TIME = 7ns MAX. INPUT IMPEDANCE = 1MΩ, 22pF.
2. RISE TIME = 10ns MAX. SOURCE IMPEDANCE = 50 Ω.

