


# New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.  
 SPRINGFIELD, NEW JERSEY 07081  
 U.S.A.

TELEPHONE: (973) 376-2922  
 (212) 227-6000  
 FAX: (973) 376-9966

50 WATTS  
 ZENER DIODES



1N2804 thru 1N2846, 1N3305 thru 1N3350, 1N4549 thru 1N4564

ELECTRICAL CHARACTERISTICS ( $T_C = 30^\circ\text{C}$  unless otherwise specified,  $V_F = 1.5\text{ V max @ } 10\text{ A}$  on all types.)

50 Watt Case 54	50 Watt Case 58	Nominal Zener Voltage @ $I_{ZT}$ ( $V_Z$ ) Volts	Test Current ( $I_{ZT}$ ) mA	Max Zener Impedance		Max DC Zener Current 75°C Case Temp ( $I_{ZM}$ ) mA	Reverse Leakage Current			Typical Zener Voltage Temp. Coeff. %/°C
				$Z_{ZT}$ @ $I_{ZT}$ ohms	$Z_{ZK}$ @ $I_{ZK} = 5\text{ mA}$ ohms		$I_{R\text{Max}}$ ( $\mu\text{A}$ )	$V_{R1}$	$V_{R2}$	
1N4557	1N4549	3.9	3200	0.16	400	11900	150	0.5	0.5	-.025
1N4558	1N4550	4.3	2900	0.16	500	10650	150	0.5	0.5	-.025
1N4559	1N4551	4.7	2650	0.12	600	9700	100	1.0	1.0	.010
1N4560	1N4552	5.1	2450	0.12	650	8900	20	1.0	1.0	.015
1N4561	1N4553	5.6	2250	0.12	900	8100	20	1.0	1.0	.030
1N4562	1N4554	6.2	2000	0.14	1000	7300	20	2.0	2.0	.040
1N2804	1N3305	6.8	1850	0.2	70	6600	150	4.5	4.3	.040
1N4563	1N4555	6.8	1850	0.16	200	6650	10	2.0	2.0	.045
1N2805	1N3306	7.5	1700	0.3	70	5900	75	5.0	4.7	.045
1N4564	1N4556	7.5	1650	0.24	100	6050	10	3.0	3.0	.053
1N2806	1N3307	8.2	1500	0.4	70	5200	50	5.4	5.2	.048
1N2807	1N3308	9.1	1370	0.5	70	4800	25	6.1	5.7	.051
1N2808	1N3309	10	1200	0.6	80	4300	10	6.7	6.3	.055
1N2809	1N3310	11	1100	0.8	80	3900	5	8.4	8.0	.060
1N2810	1N3311	12	1000	1.0	80	3600	5	9.1	8.6	.065
1N2811	1N3312	13	960	1.1	80	3300	5	9.9	9.4	.065
1N2812	1N3313	14	890	1.2	80	3000	5	10.6	10.1	.070
1N2813	1N3314	15	830	1.4	80	2800	5	11.4	10.8	.070
1N2814	1N3315	16	780	1.6	80	2650	5	12.2	11.5	.070
1N2815	1N3316	17	740	1.8	80	2500	5	13.0	12.2	.075
1N2816	1N3317	18	700	2.0	80	2300	5	13.7	13.0	.075
1N2817	1N3318	19	660	2.2	80	2200	5	14.4	13.7	.075
1N2818	1N3319	20	630	2.4	80	2100	5	15.2	14.4	.075
1N2819	1N3320	22	570	2.5	80	1900	5	16.7	15.8	.080
1N2820	1N3321	24	520	2.6	80	1750	5	18.2	17.3	.080
1N2821	1N3322	25	500	2.7	90	1550	5	19.0	18.0	.080
1N2822	1N3323	27	460	2.8	90	1500	5	20.6	19.4	.085
1N2823	1N3324	30	420	3.0	90	1400	5	22.8	21.6	.085
1N2824	1N3325	33	380	3.2	90	1300	5	25.1	23.8	.085
1N2825	1N3326	36	350	3.5	90	1150	5	27.4	25.9	.085
1N2826	1N3327	39	320	4.0	90	1050	5	29.7	28.1	.090
1N2827	1N3328	43	290	4.5	90	975	5	32.7	31.0	.090
1N2828	1N3329	45	280	4.5	100	930	5	34.2	32.4	.090
1N2829	1N3330	47	270	5.0	100	880	5	35.8	33.8	.090
1N2830	1N3331	50	250	5.0	100	830	5	38.0	36.0	.090
1N2831	1N3332	51	245	5.2	100	810	5	38.8	36.7	.090
—	1N3333	52	240	5.5	100	790	5	39.5	37.4	.090
1N2832	1N3334	56	220	6	110	740	5	42.6	40.3	.090
1N2833	1N3335	62	200	7	120	660	5	47.1	44.6	.090
1N2834	1N3336	68	180	8	140	600	5	51.7	49.0	.090
1N2835	1N3337	75	170	9	150	540	5	56.0	54.0	.090
1N2836	1N3338	82	150	11	160	490	5	62.2	59.0	.090
1N2837	1N3339	91	140	15	180	420	5	69.2	65.5	.090
1N2838	1N3340	100	120	20	200	400	5	76.0	72.0	.090
1N2839	1N3341	105	120	25	210	380	5	79.8	75.6	.095
1N2840	1N3342	110	110	30	220	365	5	83.6	79.2	.095
1N2841	1N3343	120	100	40	240	335	5	91.2	86.4	.095
1N2842	1N3344	130	95	50	275	310	5	98.8	93.6	.095
—	1N3345	140	90	60	325	290	5	106.4	100.8	.095
1N2843	1N3346	150	85	75	400	270	5	114.0	108.0	.095
1N2844	1N3347	160	80	80	450	250	5	121.6	115.2	.095
—	1N3348	175	70	85	500	230	5	133.0	126.0	.095
1N2845	1N3349	180	68	90	525	220	5	136.8	129.6	.095
1N2846	1N3350	200	65	100	600	200	5	152.0	144.0	.100




### MAXIMUM RATINGS

Junction and Storage Temperature:  $-65^\circ\text{C}$  to  $+175^\circ\text{C}$ .

DC Power Dissipation: 50 Watts. (Derate 0.5 W/°C above 75°C).

TOLERANCE DESIGNATION: The type numbers shown have a standard tolerance of  $\pm 20\%$  on the nominal zener voltage. Add suffix "A" for  $\pm 10\%$  units or "B" for  $\pm 5\%$  units. (2% and 1% tolerance also available.)

TO-3 50 mil



SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.516	1.573	38.50	39.96
B (DIA)	0.748	0.875	19.00	22.23
C	0.250	0.450	6.35	11.43
D	0.433	0.516	11.00	13.10
E	0.054	0.065	1.38	1.65
F	0.048	0.051	1.22	1.30
G	1.177	1.197	29.90	30.40
H	0.650	0.681	16.50	17.30
J	0.420	0.440	10.67	11.18
K	0.205	0.225	5.21	5.72
L (DIA)	0.151	0.172	3.84	4.36
M	0.984	1.050	25.00	26.67

TO-3 50 MIL (REV: R0)

Lead Codes

	PIN 1	PIN 2	CASE
SCR	G	C	A
Zener (B suffix)	C	C	A
Zener (RB suffix)	A	A	C

R0

- Standard voltage tolerances are +/- 5% with B suffix, +/-10% with an A suffix, and +/-20% with no suffix
- Consult factory for +/-2% or +/-1% with a C or D suffix respectively
- Reverse polarity available
- Standard polarity is anode to case
- Reverse polarity with cathode to case by designating R suffix in part number, e.g. 1N2804RB, etc.