



2SD1805

Bipolar Transistor 20V, 5A, Low VCE(sat), NPN Single TP/TP-FA

ON Semiconductor®

<http://onsemi.com>

Applications

- Strobes, voltage regulators, relay drivers, lamp drivers

Features

- Low saturation voltage
- Fast switching time
- Large current capacity
- Small and slim package making it easy to make 2SD1805-applied sets smaller


Specifications

Absolute Maximum Ratings at Ta=25°C


| Parameter | Symbol | Conditions | Ratings | Unit |
|------------------------------|------------------|----------------------|-------------|------|
| Collector-to-Base Voltage | V _{CB0} | | 60 | V |
| Collector-to-Emitter Voltage | V _{CEO} | | 20 | V |
| Emitter-to-Base Voltage | V _{EB0} | | 6 | V |
| Collector Current | I _C | | 5 | A |
| Collector Current (Pulse) | I _{CP} | | 8 | A |
| Collector Dissipation | P _C | T _c =25°C | 1 | W |
| | | | 15 | W |
| Junction Temperature | T _j | | 150 | °C |
| Storage Temperature | T _{stg} | | -55 to +150 | °C |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions unit : mm (typ) 7518-003




Package Dimensions unit : mm (typ) 7003-003



Product & Package Information


- Package : TP
- JEITA, JEDEC : SC-64, TO-251
- Minimum Packing Quantity : 500 pcs./bag

Marking (TP, TP-FA)




- Package : TP-FA
- JEITA, JEDEC : SC-63, TO-252
- Minimum Packing Quantity : 700 pcs./reel

Packing Type (TP-FA) : TL



Electrical Connection



2SD1805


Electrical Characteristics at Ta=25°C

| Parameter | Symbol | Conditions | Ratings | | | Unit |
|---|----------------------|--|---------|-----|------|------|
| | | | min | typ | max | |
| Collector Cutoff Current | ICBO | V _{CB} =50V, I _E =0A | | | 100 | nA |
| Emitter Cutoff Current | IEBO | V _{EB} =5V, I _C =0A | | | 100 | nA |
| DC Current Gain | h _{FE1} | V _{CE} =2V, I _C =500mA | 120* | | 560* | |
| | h _{FE2} | V _{CE} =2V, I _C =3A | 95 | | | |
| Gain-Bandwidth Product | f _T | V _{CE} =10V, I _C =50mA | | 120 | | MHz |
| Output Capacitance | C _{ob} | V _{CB} =10V, f=1MHz | | 45 | | pF |
| Collector-to-Emitter Saturation Voltage | V _{CE(sat)} | I _C =3A, I _B =60mA | | 220 | 500 | mV |
| Base-to-Emitter Saturation Voltage | V _{BE(sat)} | I _C =3A, I _B =60mA | | | 1.5 | V |
| Collector-to-Base Breakdown Voltage | V _{(BR)CBO} | I _C =10μA, I _E =0A | 60 | | | V |
| Collector-to-Emitter Breakdown Voltage | V _{(BR)CEO} | I _C =1mA, R _{BE} =∞ | 20 | | | V |
| Emitter-to-Base Breakdown Voltage | V _{(BR)EBO} | I _E =10μA, I _C =0A | 6 | | | V |
| Turn-On Time | t _{on} | See specified Test Circuit | | 30 | | ns |
| Storage Time | t _{stg} | | | 300 | | ns |
| Fall Time | t _f | | | 40 | | ns |

* : The 2SD1805 is classified by 500mA h_{FE} as follows.

| Rank | E | F | G |
|-----------------|------------|------------|------------|
| h _{FE} | 120 to 200 | 160 to 320 | 280 to 560 |









Switching Time Test Circuit





$$I_C = 10I_{B1} = -10I_{B2} = 2A, V_{CC} = 10V$$

Ordering Information

| Device | Package | Shipping | memo |
|---------------|---------|--------------|---------|
| 2SD1805F-E | TP | 500pcs./bag | Pb Free |
| 2SD1805G-E | TP | 500pcs./bag | |
| 2SD1805F-TL-E | TP-FA | 700pcs./reel | |
| 2SD1805G-TL-E | TP-FA | 700pcs./reel | |



2SD1805




Taping Specification

2SD1805F-TL-E, 2SD1805G-TL-E

Packing Format

| Package Name | Carrier Tape Type | Maximum Number of devices contained (pcs) | | | Packing format | |
|--------------|-------------------|---|-----------|-----------|---|--|
| | | Reel | Inner box | Outer box | Inner BOX (C-1) | Outer BOX (A-7) |
| TP-FA | TP | 700 | 2,100 | 12,600 | 3 reels contained Dimensions:mm (external) 183×72×185 | 6 inner boxes contained Dimensions:mm (external) 440×195×210 |


Packing method



Type No.
LOT No.
Quantity
Origin


Reel label

Reel label, Inner box label (unit:mm)



Outer box label

It is a label at the time of factory shipments. The form of a label may change in physical distribution process.




NOTE (1)

The LEAD FREE * description shows that the surface treatment of the terminal is lead free.


| Label | JEITA Phase |
|-------------|----------------|
| LEAD FREE 3 | JEITA Phase 3A |
| LEAD FREE 4 | JEITA Phase 3 |

Taping configuration

1. Carrier tape size (unit:mm)



2. Device placement direction




Those with one electrode terminal on the feed hole side.....TL


2SD1805

Outline Drawing

2SD1805F-TL-E, 2SD1805G-TL-E




Land Pattern Example



2SD1805

Outline Drawing

2SD1805F-E, 2SD1805G-E



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.