

## This document was generated on 04/03/2014 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>39-01-3023</u>		
Status:	Active		
Overview:	Mini-Fit Jr.™ Power Connect	ors	
Description:		Dual Row without Panel Mount Ears, PA Polyamide Nylon	
<b>_ _</b>	6/6, UL 94V-2, 2 Circuits		
	,,,		
Documents:			
3D Model		Packaging Specification PK-5559-002 (PDF)	
Drawing (PDF)		Test Summary TS-5556-002 (PDF)	
	PS-45750-001 (PDF)	RoHS Certificate of Compliance (PDF)	Series
Product Specification		······································	image - Reference only
Agency Certification			EU RoHS China RoHS
CSA		LR19980	ELV and RoHS
UL		E29179	Compliant
UL		L29179	REACH SVHC
General			Contains SVHC: No
Product Family		Crimp Housings	Low-Halogen Status
Series		5559	Low-Halogen
Application		Power, Wire-to-Board, Wire-to-Wire	
Comments		Current = 13A max. per circuit when header is mated	Need more information on product
		to a receptacle loaded with <u>45750</u> series terminals	environmental compliance?
		crimped to 16 AWG wire See Molex product	Email productcompliance@molex.com
		specification PS-45750-001 for additional current	For a multiple part number RoHS Certificate of
		derating information Glow Wire Equivalent Part.	Compliance, <u>click here</u>
MolexKits		Yes	
Overview		Mini-Fit Jr. <sup>™</sup> Power Connectors	Please visit the Contact Us section for any
Product Name		Mini-Fit Jr.™	non-product compliance questions.
UPC		800753617926	
Dhusiaal			
Physical			
Breakaway		No	Search Parts in this Series
Circuits (maximum)		2 Natural	<u>5559</u> Series
Color - Resin		Natural	
Flammability		94V-2	Mates With
Gender		Plug No	<u>39-01-3028</u> Receptacle Housing.
Glow-Wire Compliant Keying to Mating Part		None	<u>39-01-2025</u> Receptacle Housing
Lock to Mating Part		Yes	
Material - Resin		Nylon	Use With
Net Weight		0.857/g	<u>5558</u> Mini-Fit Jr. <sup>™</sup> Male Crimp Terminals.
Number of Rows		2	30490 Mini-Fit® Male Grounding Crimp
Packaging Type		Bag	Terminals
Panel Mount		No	,
Pitch - Mating Interfac	ce	4.20mm	
Pitch - Termination In		4.20mm	
Polarized to Mating P		Yes	
Stackable		No	
Temperature Range -	- Operating	-40°C to +105°C	
Electrical		104	
Current - Maximum p	er Contact	13A	
Material Info			
Old Part Number		5559-02P1	
Reference - Drawing Numbers			

Packaging Specification Product Specification Sales Drawing Test Summary

PK-5559-002 PS-45750-001, PS-5556-001 SD-5559-NP1\* TS-5556-002

## This document was generated on 04/03/2014 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION