


**5A10F-5A100F**

Plastic Silicon Rectifiers

**VOLTAGE RANGE: 100 --- 1000 V**  
**CURRENT: 5.0 A**
**ITO-220AC**

## Features

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

## Mechanical Data

- ◇ Case: JEDEC ITO-220AC, molded plastic
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.056ounces, 1.587 grams
- ◇ Mounting position: Any

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		5A10F	5A20F	5A40F	5A60F	5A80F	5A100F	UNITS
Maximum recurrent peak reverse voltage	$V_{RRM}$	100	200	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	70	140	280	420	560	700	V
Maximum DC blocking voltage	$V_{DC}$	100	200	400	600	800	1000	V
Maximum average forward rectified current 9.5mm lead length, @ $T_c=100^\circ\text{C}$	$I_{F(AV)}$	5.0						A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_j=125^\circ\text{C}$	$I_{FSM}$	300						A
Maximum instantaneous forward voltage @ 5.0 A	$V_F$	1.2						V
Maximum reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	$I_R$	10 100						$\mu\text{A}$
Typical junction capacitance (Note1)	$C_J$	80						pF
Typical thermal resistance (Note2)	$R_{\theta JC}$	10						$^\circ\text{C}/\text{W}$
Operating junction temperature range	$T_J$	-55 ---- +150						$^\circ\text{C}$
Storage temperature range	$T_{STG}$	-55 ---- +150						$^\circ\text{C}$

NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


2. Thermal resistance from junction to case.




Dimensions in millimeters

## Ratings AND Characteristic Curves


**FIG.1 – FORWARD DERATING CURVE**




**FIG.2 – TYPICAL FORWARD CHARACTERISTICS**



**FIG.3 – MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT**



**FIG.4 – TYPICAL JUNCTION CAPACITANCE**



NUMBER OF CYCLES AT 60Hz

REVERSE VOLTAGE, VOLTS