

HIGH POWER AIRCRAFT/VEHICLE DC BUS VOLTAGE SUPPRESSOR

APPLICATIONS

- ✓ DC Power Supply Protection
- ✓ MIL-STD-704 Power Bus Protection

IEC COMPATIBILITY (EN61000-4)

- ✓ 61000-4-5 (Surge): 95A, 8/20µs - Level 4 (Line-Gnd) & 48A, Level 4 (Line-Line)

FEATURES

- ✓ *Meets the Following Military Specifications:*
 - MIL-STD-704
 - MIL-PRF-19500
- ✓ 15 kilowatts Peak Pulse Power per Line (tp=10/1000µs)
- ✓ Each Device 100% Tested
- ✓ 28 Volt Power Supply Protection

MECHANICAL CHARACTERISTICS


- ✓ Molded Plastic Case
- ✓ Weight 38 grams: 704-15K36 & 65 grams: 704-15K36T (Approximate)
- ✓ Flammability Rating UL 94V-0
- ✓ Device Marking: Logo, Date Code & Part Number
- ✓ Positive Terminal Indicated By Polarity Dot
- ✓ Screening for Military Requirements IAW MIL-PRF-19500 is Available
- ✓ Screening Available Upon Request - The 704 series can be screened upon request for military requirements in accordance with MIL-PRF-19500 (applicable test). Standard screening is available based on the following options:
 - H1 - Submodule Screening per test plans 05231 & 05232
 - H2 - Submodule & Module Screening per test plan 05233
 - H3 - Submodule & Module Screening, Module Group B & C Lot Testing per test plans 05234 & 05235

15,000 WATTS



704-15K36

15,000 WATTS



704-15K36T

MAXIMUM RATINGS @ 25°C Unless Otherwise Specified


PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power (tp = 10/1000µs) - See Figure 1	P _{PP}	15	kilowatts
Operating Temperature	T _J	-55°C to 150°C	°C
Storage Temperature	T _{STG}	-55°C to 150°C	°C
Forward Surge Rating @ 25°C 1/120 seconds	F _I	300	Amps
Steady State Power Dissipation @ 25°C	T _A	10	Watts

DEVICE CHARACTERISTICS


ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified

PART NUMBER	RATED STAND-OFF VOLTAGE	MINIMUM BREAKDOWN VOLTAGE	MAXIMUM CLAMPING VOLTAGE (See Fig. 2)	MAXIMUM LEAKAGE CURRENT	MAXIMUM PEAK PULSE CURRENT (See Fig. 2)	MAXIMUM FORWARD VOLTAGE
	V_{WM} VOLTS	@ 10mA $V_{(BR)}$ VOLTS	@ I_{PPM} V_C VOLTS	@ V_{WM} I_D μA	I_{PPM} AMPS	@ 100A, 8.3ms I_F VOLTS DC
704-15K36	31.5	36	53	100	300	3.0
704-15K36T	31.5	36	53	500	300	15.0


**FIGURE 1
PEAK PULSE POWER VS PULSE TIME**



**FIGURE 2
PULSE WAVE FORM**



**FIGURE 3
POWER DERATING CURVE**



704-15K36 & 704-15k36T

PACKAGE OUTLINE & DIMENSIONS

704-15K36 PACKAGE OUTLINE				
704-15K36				
DIMENSIONS				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	49.28	51.56	1.97	2.03
B	43.92	44.96	1.73	1.77
C	2.79	3.56	0.110	0.140
D	18.29	19.81	0.72	0.78
E*	3.18 DIA	3.18 DIA	0.125 DIA	0.125 DIA
F	8.76	10.29	0.345	0.405
G	13.51	15.04	0.532	0.592
H*	0.66	0.71	0.026	0.028
I	11.94	13.46	0.47	0.53
J	2.41	2.92	0.095	0.115
K	7.70	8.20	0.303	0.323
L	9.40	10.92	0.37	0.43
704-15K36T PACKAGE OUTLINE				
704-15K36T				
DIMENSIONS				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	62.74	64.26	2.47	2.53
B	53.34	54.48	2.10	2.145
C	4.32	5.33	0.17	0.21
D	10.54	12.07	0.415	0.475
E*	3.18 DIA	3.18 DIA	0.125 DIA	0.125 DIA
F	8.26	9.27	0.325	0.365
G*	11.43	11.43	0.450	0.450
H	21.84	23.37	0.86	0.92
I*	5.59	5.59	0.220	0.220
J	16.51	17.53	0.65	0.69
K*	8.51	8.51	0.335	0.335
Note*: Dimensions are nominal				
Outline & Dimensions: Rev 1 - 4/04, 06035				

COPYRIGHT © ProTek Devices 2005

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

ProTek Devices

2929 South Fair Lane, Tempe, AZ 85282

Tel: 602-431-8101 Fax: 602-431-2288

E-Mail: sales@protekdevices.com

Web Site: www.protekdevices.com