


Voltage Mode PWM Controller

■ Features

- Complete PWM Power Control Circuitry
- Uncommitted Outputs for 200-mA Sink or Source Current
- Output Control Selects Single-Ended or Push-Pull Operation
- Internal Circuitry Prohibits Double Pulse at Either Output
- Variable Dead Time Provides Control Over Total Range
- Internal Regulator Provides a Stable 5-V Reference Supply with 3% Tolerance
- Circuit Architecture allows Easy Synchronization

■ Connection Diagram



■ Description

The AP494 incorporates on a single monolithic chip all the functions required in the construction of a pulse-width-modulation control circuit. Designed primarily for power supply control, this device offers the systems engineer the flexibility to tailor the power supply control circuitry to a specific application.


The AP494 contains two error amplifiers, one adjustable on-chip oscillator, a dead-time control (DTC) comparator, a pulse-steering control flip-flop, a 5-V, 3%-precision regulator, and output-control circuits.

The error amplifiers exhibit a common-mode voltage range from -0.3V to V_{CC} -2V. The dead-time control comparator has a fixed offset that provides approximately 5% dead time. The on-chipped oscillator may be bypassed in two ways. One is to terminate RT to the reference output and the other one is to provide a sawtooth input to CT, or it may drive the common circuits in synchronous multiple-rail power supplies.

The uncommitted output transistors provide either common-emitter or emitter-follower output capability. The AP494 provides for push-pull or single-ended output operation, which may be selected through the output-control function. The architecture of this device prohibits the possibility of either output being pulsed twice during push-pull operation.


The AP494 is characterized for operation from 0°C to 70°C.

■ Ordering Information



Voltage Mode PWM Controller

■ Functional Block Diagram



■ Absolute Maximum Ratings

Rating	Symbol	Value	Unit
Power Supply Voltage	V_{CC}	40	V
Collector Output Voltage	V_{C1}, V_{C2}	40	V
Collector Output Current (Each transistor)	I_{C1}, I_{C2}	250	mA
Amplifier Input Voltage Range	V_{IR}	-0.3 to +40	V
Power Dissipation @ $T_A \leq 45^\circ C$	P_D	1000	mW
Thermal Resistance, Junction-to-Ambient	$R_{\Theta JA}$	80	°C/W
Operating Junction Temperature	T_J	125	°C
Storage Temperature Range	T_{STG}	-55 to +125	°C
Operating Ambient Temperature Range	T_A	0 to +70	°C
Derating Ambient Temperature	T_A	45	°C

■ Recommended Operating Conditions

Characteristics	Symbol	Min	Typ	Max	Unit
Power Supply Voltage	V_{CC}	7.0	15	40	V
Collector Output Voltage	V_{C1}, V_{C2}	-	30	40	V
Collector Output Current (Each transistor)	I_{C1}, I_{C2}	-	-	200	mA
Amplified Input Voltage	V_{in}	-0.3	-	$V_{CC}-2.0$	V
Current Into Feedback Terminal	I_{fb}	-	-	0.3	mA
Reference Output Current	I_{ref}	-	-	10	mA
Timing Resistor	R_T	1.8	30	500	kΩ
Timing Capacitor	C_T	0.0047	0.001	10	μF
Oscillator Frequency	f_{osc}	1.0	40	200	kHz

Voltage Mode PWM Controller

■ Electrical Characteristics

($V_{CC}=15V$, $C_T=0.01\mu F$, $R_T=12\text{ k}\Omega$, unless otherwise noted.) For typical values $T_A=25^\circ C$, for min/max values T_A is the operating ambient temperature range that applies, unless otherwise noted)

Characteristics	Symbol	Min	Typ	Max	Unit
REFERENCE SECTION					
Reference Voltage ($I_O=1.0\text{mA}$)	V_{ref}	4.85	5.0	5.15	V
Line Regulation ($V_{CC}=7.0\text{ V}$ to 40V)	Reg_{line}	-	2.0	25	mV
Load Regulation ($I_O=1.0\text{mA}$ to 20mA)	Reg_{load}	-	3.0	15	mV
Short Circuit Output Current ($I_{ref}=0\text{ V}$)	I_{SC}	4.5	60	75	mA

OUTPUT SECTION

Collector Off-State Current ($V_{CC}=40\text{V}$, $V_{CE}=40\text{V}$)	$I_{C(off)}$	-	2.0	100	μA
Emitter Off-State Current ($V_{CC}=40\text{V}$, $V_C=40\text{V}$, $V_E=0\text{V}$)	$I_{E(off)}$	-	-	-100	μA
Collector-Emitter Saturation Voltage (Note 1) Common-Emitter ($V_E=0\text{V}$, $I_C=200\text{mA}$) Emitter-Follower ($V_C=15\text{V}$, $I_E=-200\text{mA}$)	$V_{sat(C)}$ $V_{sat(E)}$	- -	1.1 1.5	1.5 2.5	V
Output Control Pin Current Low State ($V_{OC}\leq 0.4\text{V}$) High State ($V_{OC}=V_{ref}$)	I_{OCL} I_{OCH}	- -	10 0.2	- 3.5	μA mA
Output Voltage Rise Time Common-Emitter (See Figure 4) Emitter-Follower (See Figure 5)	t_r	- -	100 100	200 200	ns
Output Voltage Fall Time Common-Emitter (See Figure 4) Emitter-Follower (See Figure 5)	t_f	- -	25 40	100 100	ns

NOTE: 1. Low duty cycle pulse techniques are used during test to maintain junction temperature as close to ambient temperature as possible.

ERROR AMPLIFIER SECTION

Input Offset Voltage ($V_{O(Pin\ 3)}=2.5\text{V}$)	V_{IO}	-	2.0	10	mV
Input Offset Current ($V_{O(Pin\ 3)}=2.5\text{V}$)	I_{IO}	-	5.0	250	nA
Input Bias Current ($V_{O(Pin\ 3)}=2.5\text{V}$)	I_{IB}	-	-0.1	-0.1	μA
Input Common Mode Voltage Range ($V_{CC}=40\text{V}$, $T_A=25^\circ C$)	V_{ICR}	-0.3 to $V_{CC}-2.0$			V
Open Loop Voltage Gain ($\Delta V_O=3.0\text{V}$, $V_O=0.5\text{V}$ to 3.5V , $R_L=2.0\text{ k}\Omega$)	A_{VOL}	70	95	-	dB
Unity-Gain Crossover Frequency ($V_O=0.5\text{V}$ to 3.5V , $R_L=2.0\text{ k}\Omega$)	f_c	-	350	-	kHz
Common Mode Rejection Ratio ($V_{CC}=40\text{V}$)	$CMRR$	64	90	-	dB
Output Sink Current ($V_{O(Pin\ 3)}=0.7\text{V}$)	I_{O-}	0.3	0.7	-	mA
Output Source Current ($V_{O(Pin\ 3)}=3.5\text{V}$)	I_{O+}	-10	-15	-	mA

PWM COMPARATOR SECTION (Test Circuit Figure 1)

Input Threshold Voltage (Zero Duty Cycle)	V_{TH}	-	4	4.5	V
Input Sink Current ($V_{(Pin\ 3)}=0.7\text{V}$)	I_{I-}	0.3	0.7	-	mA

DEADTIME CONTROL SECTION (Test Circuit Figure 1)

Input Bias Current (Pin 4) ($V_{Pin4}=0\text{V}$ to 5.25V)	$I_{IB(DT)}$	-	-2.0	-10	μA
Maximum Duty Cycle, Each Output, Push-Pull Mode ($V_{Pin4}=0\text{V}$, $C_T=0.01\mu F$, $R_T=12\text{ k}\Omega$)	DC_{max}	45	48	50	%
Input Threshold Voltage (Pin 4) (Zero Duty Cycle) (Maximum Duty Cycle)	V_{th}	- 0	2.8 -	3.3 -	V

Voltage Mode PWM Controller

■ Electrical Characteristics(Continued)


($V_{CC}=15V$, $C_T=0.01\mu F$, $R_T=12\text{ k}\Omega$, unless otherwise noted.) For typical values $T_A=25^\circ C$, for min/max values T_A is the operating ambient temperature range that applies, unless otherwise noted)

Characteristics	Symbol	Min	Typ	Max	Unit
OSCILLATOR SECTION					
Frequency ($C_T=0.01\mu F$, $R_T=12\text{ k}\Omega$)	f_{osc}	-	10	-	kHz
Standard Deviation of Frequency* ($C_T=0.001\mu F$, $R_T=30\text{ k}\Omega$)	σf_{osc}	-	3.0	-	%
Frequency Change with Voltage ($V_{CC}=7.0V$ to $40V$, $T_A=25^\circ C$)	$\Delta f_{osc} (\Delta V)$	-	0.1	-	%
Frequency Change with Temperature ($\Delta T_A=T_{low}$ to T_{high}) ($C_T=0.01\mu F$, $R_T=12\text{ k}\Omega$)	$\Delta f_{osc} (\Delta T)$	-	-	12	%
TOTAL DEVICE					
Standby Supply Current(Pin6 at V_{ref} , All other inputs and outputs open) ($V_{CC}=15V$) ($V_{CC}=40V$)	I_{CC}	-	5.5 7.0	10 15	mA
Average Supply Current ($C_T=0.01\mu F$, $R_T=12\text{ k}\Omega$, $V_{(Pin4)}=2.0V$) ($V_{CC}=15V$) (See Figure 4)		-	7.0	-	mA

*Standard deviation is a measure of the statistical distribution about the mean as derived from the formula,

$$\sigma = \sqrt{\frac{\sum_{n=1}^N (X_n - \bar{X})^2}{N-1}}$$

Figure 1. PARAMETER MEASUREMENT INFORMATION



Voltage Mode PWM Controller

Figure 2. OPERATIONAL TEST CIRCUIT AND WAVEFORMS




Figure 3. AMPLIFIER CHARACTERISTICS







Figure 4. COMMON-EMITTER CONFIGURATION



NOTE A. CL includes probe and jig capacitance.

Voltage Mode PWM Controller

Figure 5. Emitter-Follower Configuration



NOTE A. CL includes probe and jig capacitance.

Figure 6.




Figure 7.




Figure 8.





Figure 9.



Voltage Mode PWM Controller

Figure 10.

Common-Emitter Configuration Output Saturation Voltage versus Collector Current




Figure 11.

Standby Supply Current versus Supply Voltage






Figure 12.

Oscillator Frequency versus Timing Resistance




■ Marking Information



■ Package Dimension


(1) Package Type: SOP-16L



Symbol	Dimensions In Millimeters			Dimensions In Inches		
	Min.	Nom.	Max.	Min.	Nom.	Max.
A	1.40	1.60	1.75	0.055	0.063	0.069
A1	0.10	-	0.25	0.040	-	0.010
A2	1.30	1.45	1.50	0.051	0.057	0.059
B	0.33	0.41	0.51	0.013	0.016	0.020
C	0.19	0.20	0.25	0.0075	0.008	0.0098
D	9.80	9.90	10.00	0.386	0.390	0.394
E	3.80	3.90	4.00	0.150	0.154	0.157
e	-	1.27	-	-	0.050	-
H	5.80	6.00	6.20	0.228	0.236	0.244
L	0.38	0.71	1.27	0.015	0.028	0.050
Θ	0	-	8	0	-	8

■ Package Information (Continued)

(2) Package Type: PDIP-16L



Symbol	Dimensions In Millimeters			Dimensions In Inches		
	Min.	Nom.	Max.	Min.	Nom.	Max.
A	-	-	4.57	-	-	0.180
A1	0.38	-	-	0.015	-	-
A2	3.15	3.33	3.50	0.124	0.131	0.138
B	0.36	0.46	0.56	0.014	0.018	0.022
B1	1.14	1.27	1.52	0.045	0.050	0.060
B2	0.81	0.99	1.17	0.032	0.039	0.046
C	0.20	0.25	0.33	0.008	0.010	0.013
D	18.90	19.10	19.30	0.744	0.752	0.760
D1	0.56	0.69	0.76	0.022	0.027	0.030
E	7.62	-	8.26	0.3000	-	0.325
E1	6.15	6.35	6.55	0.242	0.250	0.258
e	-	2.54	-	-	0.100	-
L	2.92	-	3.81	0.115	-	0.150
eB	8.38	-	9.40	0.330	-	0.370