

AR/ARS35X SERIES

HIGH CURRENT PLASTIC SILICON RECTIFIER

产

品

规

格

确

认

书

AR/ARS35005 THRU AR/ARS3510

HIGH CURRENT PLASTIC SILICON RECTIFIER




REVERSE VOLTAGE: 50 to 1000 VOLTS
FORWARD CURRENT: 35.0 AMPERE

FEATURES

- Plastic material has Underwriters Laboratory Flammability Classification 94V-0
- Low cost construction utilizing void-free molded plastic technique
- Low cost
- Diffused junction
- High surge current capability
- Low leakage
- High temperature soldering guaranteed: 250°C for 10 seconds

MECHANICAL DATA

Case: Molded plastic, RA/RAS
 Epoxy: UL 94V-O rate flame retardant
 Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
 Polarity: Color ring denotes cathode end
 Mounting position: Any
 Weight: 0.07ounce, 1.8gram



Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

	Symbols	AR35005	AR3501	AR3502	AR3504	AR3506	AR3508	AR3510	Units
		ARS35005	ARS3501	ARS3502	ARS3504	ARS3506	ARS3508	ARS3510	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current at $T_C=150^\circ\text{C}$	$I_{(AV)}$	35							Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	500							Amp
Maximum Forward Voltage at 35.0A DC and 25°C	V_F	1.0							Volts
Maximum Reverse Current at $T_C=25^\circ\text{C}$ at Rated DC Blocking Voltage $T_C=100^\circ\text{C}$	I_R	5.0 250							uAmp
Typical Junction Capacitance (Note 1)	C_J	300							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JC}$	1							°C/W
Maximum Reverse Recovery Time (Note 3)	T_{RR}	3							uS
Operating and Storage Temperature Range	T_J, T_{stg}	-55 to +175							°C

NOTES:

- 1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.
- 2- Reverse Recovery Test Conditions: $I_F=5A$, $I_R=1A$, $I_{RR}=.25A$.
- 3- Thermal Resistance from Junction to Case, Single Side Cooled.

AR/ARS35005 THRU AR/ARS3510 HIGH CURRENT PLASTIC SILICON RECTIFIER



RATINGS AND CHARACTERISTIC CURVES

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE

