


## Ultra High Precision Bulk Metal® Z-Foil Extended Value Range Resistor, with TCR of 0.2 ppm/°C, PCR of 5 ppm Rated Power, Tolerance to 0.005 %, and Power Rated at 0.6 W



### Any value available within resistance range

The Z-foil technology provides a significant reduction of the resistive component's sensitivity to ambient temperature variations (TCR) and applied power changes (PCR).



Designers can now guarantee a high degree of stability and accuracy in fixed-resistor applications using solutions based on Vishay's revolutionary Z-foil technology.

The E102Z (0.150" lead spacing) and E102JZ (0.200" lead spacing) extends the range of the ultra high precision Z201 and Z201L.

Our application engineering department is available to advise and to make recommendations. For non-standard technical requirements and special applications, please contact us.



### FEATURES

- Temperature coefficient of resistance (TCR):  
- 55 °C to + 125 °C, + 25 °C ref.  
0.2 ppm/°C typical
- Rated power: to 0.3 W at + 125 °C, 0.6 W at + 70 °C
- Tolerance: ± 0.005 %
- Load life stability: to ± 0.005 % at 70 °C, 2000 h at rated power
- Resistance range: 100 kΩ to 250 kΩ (higher and lower values of resistance are available)
- Electrostatic discharge (ESD) above 25 000 V
- Non inductive, non capacitive design
- Rise time: 1 ns without ringing
- Current noise: < - 40 dB
- Thermal EMF: 0.05 μV/°C typical
- Voltage coefficient < 0.1 ppm/V
- Low inductance: < 0.08 μH typical
- Non hot spot design
- Terminal finishes available: lead (Pb)-free tin/lead alloy
- Matched sets are available on request (TCR tracking: to 0.5 ppm/°C)

**FIGURE 1 - TYPICAL TCR CURVE Z-FOIL**

**FIGURE 2 - POWER DERATING CURVE**

**TABLE 1 - E102Z SPECIFICATIONS**

<b>Temperature Coefficient of Resistance (TCR)</b> - 55 °C to + 125 °C, + 25 °C ref.	0.2 ppm/°C typical, 0.8 ppm/°C maximum
<b>Stability</b> Load life at 2000 h  Load life at 10 000 h	± 0.005 % maximum ΔR at 0.1 W/+ 70 °C ± 0.015 % maximum ΔR at 0.3 W/+ 125 °C ± 0.01 % maximum ΔR at 0.05 W/+ 125 °C ± 0.05 % maximum ΔR at 0.3 W/+ 125 °C
<b>Current Noise</b>	< - 40 dB
<b>High Frequency Operation</b> Rise time Inductance (L) Capacitance (C)	1.0 ns 0.1 μH maximum; 0.08 μH typical 1.0 pF maximum; 0.5 pF typical
<b>Voltage Coefficient</b>	< 0.1 ppm/V
<b>Thermal EMF</b>	0.1 μV/°C maximum; 0.05 μV/°C typical

Vishay Foil Resistors Ultra High Precision Bulk Metal® Z-Foil Extended Value Range Resistor, with TCR of  $0.2 \text{ ppm}/^\circ\text{C}$ , PCR of 5 ppm Rated Power, Tolerance to  $0.005 \%$ , and Power Rated at  $0.6 \text{ W}$



**TABLE 2 - GLOBAL PART NUMBER INFORMATION**

NEW GLOBAL PART NUMBER: Y1183150K000T9L (preferred part number format)

DENOTES PRECISION Y	VALUE K = kΩ	AER* 0 = standard part, tin/lead termination 9 = standard part, lead (Pb)-free termination 1 - 999 = custom
Y 1 1 8 3	1 5 0 K 0 0 0	T 9 L
PRODUCT CODE 1183 = E102Z 1182 = E102JZ	RESISTANCE TOLERANCE V = $\pm 0.005 \%$ T = $\pm 0.01 \%$ Q = $\pm 0.02 \%$ A = $\pm 0.05 \%$ B = $\pm 0.1 \%$ C = $\pm 0.25 \%$ D = $\pm 0.5 \%$ F = $\pm 1.0 \%$	PACKAGING L = bulk pack

FOR EXAMPLE: ABOVE GLOBAL ORDER Y1183 150K000 T 9 L:  
TYPE: E102Z  
VALUE: 150.0 kΩ  
ABSOLUTE TOLERANCE:  $\pm 0.01 \%$   
TERMINATION: lead (Pb)-free  
PACKAGING: bulk pack

HISTORICAL PART NUMBER: E102Z T 150K00 T B (will continue to be used)

E102Z MODEL E102Z E102JZ	T TERMINATION T = lead (Pb)-free None = tin/lead alloy	150K00 OHMIC VALUE 150K00 = 150.0 kΩ	T RESISTANCE TOLERANCE V = $\pm 0.005 \%$ T = $\pm 0.01 \%$ Q = $\pm 0.02 \%$ A = $\pm 0.05 \%$ B = $\pm 0.1 \%$ C = $\pm 0.25 \%$ D = $\pm 0.5 \%$ F = $\pm 1.0 \%$	B PACKAGING B = bulk pack
-----------------------------------	---	--	---	---------------------------------

**Note**

\* Application engineering release: for non-standard requests, please contact application engineering.



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.