


SWITCHING REGULATOR APPLICATION.
HIGH VOLTAGE AND HIGH SPEED
SWITCHING APPLICATION.

FEATURES

- Excellent Switching Times
: $t_{on}=1.1\mu S(\text{Max.})$, $t_f=0.7\mu S(\text{Max.})$, at $I_C=1.5A$
- High Collector Voltage : $V_{CBO}=700V$.

MAXIMUM RATING ($T_a=25^\circ C$)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CBO}	700	V
Collector-Emitter Voltage	V_{CEO}	400	V
Emitter-Base Voltage	V_{EBO}	9	V
Collector Current	DC	I_C	A
	Pulse	I_{CP}	
Collector Power Dissipation	I_B	0.75	A
Collector Power Dissipation	P_C	1.5	W
Junction Temperature	T_j	150	$^\circ C$
Storage Temperature Range	T_{stg}	-55~150	$^\circ C$



ELECTRICAL CHARACTERISTICS ($T_a=25^\circ C$ unless otherwise specified)

Parameter	symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=5mA, I_E=0$	700			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=10mA, I_B=0$	400			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=2mA, I_C=0$	9			V
Collector cut-off current	I_{CBO}	$V_{CB}=700V, I_E=0$			1	mA
Collector cut-off current	I_{CEO}	$V_{CE}=400V, I_B=0$			0.5	mA
Emitter cut-off current	I_{EBO}	$V_{EB}=9V, I_C=0$			1	mA
DC current gain	h_{FE1}	$V_{CE}=5V, I_C=0.2A$	8		40	
	h_{FE2}	$V_{CE}=5V, I_C=1.5A$	5			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=1A, I_B=0.25A$			0.6	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C=1A, I_B=0.25A$			1.2	V
Transition frequency	f_T	$V_{CE}=10V, I_C=100mA, f=1MHz$	5			MHz
Fall time	t_f	$I_C=1A, I_{B1}=-I_{B2}=0.2A, V_{CC}=100V$			0.5	μs
Storage time	t_s	$I_C=250mA (UI9600)$	2		4	μs

CLASSIFICATION OF $h_{FE(1)}$

Range	10- 15	15- 20	20- 25	25- 30	30- 35	35- 40

