

## MS-106-3

Miniature Reed Sensor • pitch 15.24 mm



### Electrical Characteristics

Contact form		A
Contact rating max.	W / VA	10
Switching current max.	A	0.7
Carry current max.	A	1.0
Switching voltage max.	VDC	180
	VAC	130
Breakdown voltage min.	VDC	200
Contact resistance (initial) max.	mΩ	100
Insulation resistance min.	Ω	10 <sup>9</sup>
Capacitance typ.	pF	0.5

### Magnetical Characteristics

Pull in range available <sup>1</sup>	AT	10-25
--------------------------------------	----	-------


<sup>1</sup> AT range stated for unmodified Reed Switch

### Operating Characteristics

Operate time (incl. bounce) max.	ms	0.5
Release time max.	ms	0.3
Switching frequency max.	Hz	500
Resonant frequency typ.	Hz	5,000
Vibration (50-2000 Hz)	g	20
Shock (1/2 sin 11 ms)	g	50
Operating temperature	°C	-20 to +85

### Dimensions

in mm



### Ordering Information

Series	AT Range
MS-106-3	1 = 10-15 / 2 = 15-20 / 3 = 20-25

Ordering example: MS-106-3-2 describes MS-106-3 with 15-20 AT

Customized types available.