




MV3 & MV5 Series

5x7 mm, 3.3 or 5.0 Volt, HCMOS, VCXO



- General purpose VCXO with good performance at an affordable price



Pin Connections

PIN	FUNCTION
1	Control Voltage
2	N/C or Tristate
3	Ground
4	Output
5	N/C
6	+Vdd

Ordering Information

Product Series	MV3/MV5	1	3	V	C	N	00.0000 MHz
MV3 = 3.3 Volt MV5 = 5.0 Volt							
Temperature Range							
1: 0°C to +70°C 2: -40°C to +85°C 6: -20°C to +70°C							
Stability							
3: ±100 ppm 4: ±50 ppm 6: ±25 ppm* 8: ±20 ppm*							
Output Type							
V: Voltage Controlled - no tristate T: Voltage Controlled - tristate							
Symmetry/Logic Compatibility							
C: 45/55 CMOS G: 40/60 CMOS							
Package/Lead Configurations							
N: Leadless Ceramic							
Frequency (customer specified)							

*Consult Factory for availability

PARAMETER	Symbol	Min.	Typ.	Max	Units	Condition/Notes	
Frequency Range	F	1.544		167	MHz	MV3 See Note 4 MV5 See Note 4	
Operating Temperature	T _A	(See ordering information)					
Storage Temperature	T _S	-45		+95	°C		
Frequency Stability	ΔF/F	(See ordering information)					
Aging							
1 st Year		-3/-5		+3/+5	ppm	< 52 MHz / ≥ 52 MHz	
Thereafter (per year)		-1/-2		+1/+2	ppm	< 52 MHz / ≥ 52 MHz	
Pullability		±80			ppm	Over control voltage	
Control Voltage	V _c	0.3	1.65	3.0	V	MV3	
		0.5	2.5	4.5	V	MV5	
Linearity				15	%	Positive Monotonic Slope	
Modulation Bandwidth	f _m	10			kHz	-3 dB bandwidth	
Input Impedance	Z _{in}	50k			Ohms		
Input Voltage	V _{dd}	3.135	3.3	3.465	V	MV3	
		4.5	5.0	5.5	V	MV5	
Input Current	I _{dd}						
1.544 to 36 MHz				20	mA	MV3	
36 to 167 MHz				50	mA	MV3	
1.544 to 50 MHz				35	MA	MV5	
Output Type						HCMOS	
Load				15	pF	See Note 1	
Symmetry (Duty Cycle)		(See ordering information)					50% V _{dd} Level
Logic "1" Level	V _{oh}	90			% V _{dd}	HCMOS load	
Logic "0" Level	V _{ol}			10	% V _{dd}	HCMOS load	
Rise/Fall Time	T _r /T _f					See Note 2	
1.544 to 60 MHz				5	ns	MV3	
60 to 167 MHz				2	ns	MV3	
1.544 to 50 MHz				5	ns	MV5	
Tristate Function		Input Logic "1" or floating: output active Input Logic "0": output disables to high-Z					
Start up Time			4		ms		
Phase Jitter	φ _J					See Note 3	
20 - 45 MHz		0.5	1.0		ps RMS	Integrated 12 kHz - 20 MHz	
45 - 167 MHz		3.0	5.0		ps RMS	Integrated 12 kHz - 20 MHz	
Phase Noise (Typical)		10 Hz	100 Hz	1 kHz	10 kHz	100 kHz	
@ 19.44 MHz		-70	-100	-132	-140	-150	
						Offset from carrier dBc/Hz	

- See load circuit diagram #2.
- Rise/Fall times are measured between 10% V_{dd} and 90% V_{dd} with HCMOS load.
- Contact factory for non-standard jitter requirements.
- Contact factory for frequencies outside of the ranges shown.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

MtronPTI Lead Free Solder Profile

