




FEATURES

- Glass passivated junction
- 400 Watts Pulse capability on 10/1000 μ s wave form
- Excellent clamping capability
- Low zener impedance
- Fast response time
- High temperature soldering guaranteed: 260°C/10 seconds at terminals
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

MECHANICAL DATA

- Case: JEDEC DO-41 molded plastic body
- Terminals: Plated axial leads, solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end
- Weight: 0.012ounce, 0.33 gram

DO-41



Dimensions in inches and (millimeters)

DEVICES FOR BIDIRECTIONAL APPLICATIONS

1. For bi-directional use C or CA suffix for Types P4KE6. 8 thru Types P4KE440.
2. Electrical characteristics apply in both directions.

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating at 25 °C ambient temperature unless otherwise specified)

	Symbols	Value	Units
Peak power dissipation at $T_A=25^{\circ}\text{C}$, $T_P=1\text{ms}$ (Note 1.)	P_{PK}	Min. 400	Watts
Steady state power dissipation at $T_J=75^{\circ}\text{C}$ lead length 0. 375"(9. 5mm) (Note 2.)	P_D	1. 0	Watts
Peak forward surge current, 8. 3ms single half sine-wave superimposed on rated load(JEDEC method)(Note 3.)	I_{FSM}	40. 0	Amps
Maximum instantaneous forward voltage at 25. 0A for unidirectional only(Note 4.)	V_F	3. 5/6. 5	Volts
Operating and storage temperature range	T_J, T_{STG}	-55 to +175	$^{\circ}\text{C}$

Note: 1.Non repetitive current pulse and derated above $T_A=25^{\circ}\text{C}$

2.Mounted on copper pads area of 1. 6X1. 6"(40X40mm)

3.Measured on 8.3ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum

4. $V_F=3.5$ Volts max. for devices of $V_{(BR)} \leq 200\text{V}$, and $V_F=6.5$ Volts max. for devices of $V_{(BR)} > 200\text{V}$.

RATINGS AND CHARACTERISTIC CURVES(P4KE6.8 THRU P4KE440)

TYPE	Breakdown Voltage V _(BR) (Volts)		Test Current I _T (mA)	Reverse Stand off Voltage V _{WM} (Volts)	Maximum Reverse Leadage At V _{WM} I _D (μA)	Maximum Peak Pulse Current I _{ppm} (Amps)	Maximum Clamping Voltage At I _{ppm} V _C (Volts)	Maximum Temperature Coefficient of V _(BR) % / °C
	MIN	MAX						
*P4KE6.8	6.12	7.48	10.0	5.50	1,000.0	38.0	10.8	0.057
*P4KE6.8A	6.45	7.14	10.0	5.80	1,000.0	40.0	10.5	0.057
P4KE7.5	6.75	8.25	10.0	6.05	500.0	35.0	11.7	0.061
P4KE7.5A	7.13	7.88	10.0	6.40	500.0	37.0	11.3	0.061
P4KE8.2	7.38	9.02	10.0	6.63	200.0	33.0	12.5	0.065
P4KE8.2A	7.79	8.61	10.0	7.02	200.0	34.0	12.1	0.065
P4KE9.1	8.19	10.0	1.0	7.37	50.0	30.0	13.8	0.068
P4KE9.1A	8.65	9.55	1.0	7.78	50.0	31.0	13.4	0.068
P4KE10	9.00	11.0	1.0	8.10	10.0	28.0	15.0	0.073
P4KE10A	9.50	10.5	1.0	8.55	10.0	29.0	14.5	0.073
P4KE11	9.90	12.1	1.0	8.92	5.0	26.0	16.2	0.075
P4KE11A	10.5	11.6	1.0	9.40	5.0	27.0	15.6	0.075
P4KE12	10.8	13.2	1.0	9.72	5.0	24.0	17.3	0.078
P4KE12A	11.4	12.6	1.0	10.2	5.0	25.0	16.7	0.078
P4KE13	11.7	14.3	1.0	10.5	5.0	22.0	19.0	0.081
P4KE13A	12.4	13.7	1.0	11.1	5.0	23.0	18.2	0.081
P4KE15	13.5	16.5	1.0	12.1	5.0	19.0	22.0	0.084
P4KE15A	14.3	15.8	1.0	12.8	5.0	20.0	21.2	0.084
P4KE16	14.4	17.6	1.0	12.9	5.0	17.8	23.5	0.086
P4KE16A	15.2	16.8	1.0	13.6	5.0	18.6	22.5	0.086
P4KE18	16.2	19.8	1.0	14.5	5.0	16.0	26.5	0.088
P4KE18A	17.1	18.9	1.0	15.3	5.0	16.5	25.5	0.088
P4KE20	18.0	22.0	1.0	16.2	5.0	14.0	29.1	0.090
P4KE20A	19.0	21.0	1.0	17.1	5.0	15.0	27.7	0.090
P4KE22	19.8	24.2	1.0	17.8	5.0	13.0	31.9	0.092
P4KE22A	20.9	23.1	1.0	18.8	5.0	13.7	30.6	0.092
P4KE24	21.6	26.4	1.0	19.4	5.0	12.0	34.7	0.094
P4KE24A	22.8	25.2	1.0	20.5	5.0	12.6	33.2	0.094
P4KE27	24.3	29.7	1.0	21.8	5.0	10.7	39.1	0.096
P4KE27A	25.7	28.4	1.0	23.1	5.0	11.0	37.5	0.096
P4KE30	27.0	33.0	1.0	24.3	5.0	9.6	43.5	0.097
P4KE30A	28.5	31.5	1.0	25.6	5.0	10.0	41.4	0.097
P4KE33	29.7	36.3	1.0	26.8	5.0	8.8	47.7	0.098
P4KE33A	31.4	34.7	1.0	28.2	5.0	9.0	45.7	0.098
P4KE36	32.4	39.6	1.0	29.1	5.0	8.0	52.0	0.099
P4KE36A	34.2	37.8	1.0	30.8	5.0	8.4	49.9	0.099
P4KE39	35.1	42.9	1.0	31.6	5.0	7.4	56.4	0.100
P4KE39A	37.1	41.0	1.0	33.3	5.0	7.7	53.9	0.100
P4KE43	38.7	47.3	1.0	34.8	5.0	6.7	61.9	0.101
P4KE43A	40.9	45.2	1.0	36.8	5.0	7.0	59.3	0.101
P4KE47	42.3	51.7	1.0	38.1	5.0	6.2	67.8	0.101
P4KE47A	44.7	49.4	1.0	40.2	5.0	6.4	64.8	0.101
P4KE51	45.9	56.1	1.0	41.3	5.0	5.7	73.5	0.102
P4KE51A	48.5	53.6	1.0	43.6	5.0	6.0	70.1	0.102
P4KE56	50.4	61.6	1.0	45.4	5.0	5.2	80.5	0.103
P4KE56A	53.2	58.8	1.0	47.8	5.0	5.4	77.0	0.103

RATINGS AND CHARACTERISTIC CURVES (P4KE6.8 THRU P4KE440)

TYPE	Breakdown Voltage V _(BR) (Volts)		Test Current I _T (mA)	Reverse Stand off Voltage V _{WM} (Volts)	Maximum Reverse Leadage At V _{WM} I _D (μA)	Maximum Peak Pulse Current I _{ppm} (Amps)	Maximum Clamping Voltage At I _{ppm} V _C (Volts)	Maximum Temperature Coefficient of V _(BR) % / °C
	MIN	MAX						
P4KE62	55.8	68.2	1.0	50.2	5.0	4.7	89.0	0.104
P4KE62A	58.9	65.1	1.0	53.0	5.0	5.0	85.0	0.104
P4KE68	61.2	74.8	1.0	55.1	5.0	4.2	98.0	0.104
P4KE68A	64.6	71.4	1.0	58.1	5.0	4.5	92.0	0.104
P4KE75	67.5	82.5	1.0	60.7	5.0	3.8	108.0	0.105
P4KE75A	71.3	78.8	1.0	64.1	5.0	4.0	103.0	0.105
P4KE82	73.8	90.2	1.0	66.4	5.0	3.5	118.0	0.105
P4KE82A	77.9	86.1	1.0	70.1	5.0	3.7	113.0	0.105
P4KE91	81.9	100	1.0	73.7	5.0	3.2	131.0	0.106
P4KE91A	86.5	95.5	1.0	77.8	5.0	3.3	125.0	0.106
P4KE100	90.0	110	1.0	81.0	5.0	2.9	144.0	0.106
P4KE100A	95.0	105	1.0	85.5	5.0	3.0	137.0	0.106
P4KE110	99.0	121	1.0	89.2	5.0	2.6	158.0	0.107
P4KE110A	105	116	1.0	94.0	5.0	2.7	152.0	0.107
P4KE120	108	132	1.0	97.2	5.0	2.4	173.0	0.107
P4KE120A	114	126	1.0	102	5.0	2.5	165.0	0.107
P4KE130	117	143	1.0	105	5.0	2.2	187.0	0.107
P4KE130A	124	137	1.0	111	5.0	2.3	179.0	0.107
P4KE150	135	165	1.0	121	5.0	1.9	215.0	0.108
P4KE150A	143	158	1.0	128	5.0	2.0	207.0	0.108
P4KE160	144	176	1.0	130	5.0	1.8	230.0	0.108
P4KE160A	152	168	1.0	136	5.0	1.9	219.0	0.108
P4KE170	153	187	1.0	138	5.0	1.7	244.0	0.108
P4KE170A	162	179	1.0	145	5.0	1.8	234.0	0.108
P4KE180	162	198	1.0	146	5.0	1.6	258.0	0.108
P4KE180A	171	189	1.0	154	5.0	1.7	246.0	0.108
P4KE200	180	220	1.0	162	5.0	1.4	287.0	0.108
P4KE200A	190	210	1.0	171	5.0	1.51	274.0	0.108
P4KE220	198	242	1.0	175	5.0	1.2	344.0	0.108
P4KE220A	209	231	1.0	185	5.0	1.3	328.0	0.108
P4KE250	225	275	1.0	202	5.0	1.1	360.0	0.110
P4KE250A	237	263	1.0	214	5.0	1.2	344.0	0.110
P4KE300	270	330	1.0	243	5.0	0.97	430.0	0.110
P4KE300A	285	315	1.0	256	5.0	1.0	414.0	0.110
P4KE350	315	385	1.0	284	5.0	0.83	504.0	0.110
P4KE350A	332	368	1.0	300	5.0	0.87	482.0	0.110
P4KE400	360	440	1.0	324	5.0	0.73	574.0	0.110
P4KE400A	380	420	1.0	342	5.0	0.76	548.0	0.110
P4KE440	396	484	1.0	356	5.0	0.66	631.0	0.110
P4KE440A	418	462	1.0	376	5.0	0.69	602.0	0.110

Notes: 1. V_(BR) measured after I_T applied for 300μS, I_T=square wave pulse or equivalent.

2. For bidirectional types having V_{WM} of 10 Volts and less, The I_D limit is doubled.

RATINGS AND CHARACTERISTIC CURVES (P4KE6.8 THRU P4KE440)

FIG. 1-PEAK PULSE POWER CURVE




FIG. 2-PULSE DERATING CURVE




FIG. 3-PULSE WAVEFORM




FIG. 4-STeady STATE POWER DERATING CURVE




FIG. 5-TYPICAL JUNCTION CAPACITANCE UNIDIRECTIONAL




FIG. 6-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT UNIDIRECTIONAL

