


PM25RSB120

FLAT-BASE TYPE
INSULATED PACKAGE



Outline Drawing and Circuit Diagram

| Dimensions | Inches | Millimeters |
|------------|--------------|-------------|
| A | 3.96 ± 0.04 | 100.5 ± 1.0 |
| B | 3.48 ± 0.02 | 88.5 ± 0.5 |
| C | 2.76 ± 0.04 | 70.0 ± 1.0 |
| D | 2.30 ± 0.02 | 58.5 ± 0.5 |
| E | 1.191 ± 0.02 | 30.25 ± 0.5 |
| F | 0.83 | 21.0 |
| G | 0.75 | 19.0 |
| H | 0.73 | 18.5 |
| J | 0.71 | 18.0 |
| K | 0.69 | 17.5 |
| L | 0.67 | 17.0 |
| M | 0.581 | 14.76 |
| N | 0.541 | 13.75 |
| P | 0.541 | 13.74 |

| Dimensions | Inches | Millimeters |
|------------|---------------|--------------|
| Q | 0.41 | 10.5 |
| R | 0.39 | 10.0 |
| S | 0.394 ± 0.010 | 10.00 ± 0.25 |
| T | 0.39 Dia. | Dia. 10.0 |
| U | 0.364 | 9.25 |
| V | 0.24 | 6.0 |
| W | 0.18 Dia. | Dia. 4.5 |
| X | 0.16 | 4.0 |
| Y | 0.12 | 3.0 |
| Z | 0.88 ± 0.02 | 2.25 ± 0.5 |
| AA | 0.086 ± 0.02 | 2.18 ± 0.5 |
| AB | 0.079 ± 0.010 | 2.00 ± 0.25 |
| AC | 0.06 | 1.5 |
| AD | 0.01 ± 0.02 | 0.25 ± 0.5 |



Description:

Mitsubishi Intelligent Power Modules are isolated base modules designed for power switching applications operating at frequencies to 20 kHz. Built-in control circuits provide optimum gate drive and protection for the IGBT and free-wheel diode power devices.

Features:

- Complete Output Power Circuit
- Gate Drive Circuit
- Protection Logic
 - Short Circuit
 - Over Current
 - Over Temperature
 - Under Voltage

Applications:

- Inverters
- UPS
- Motion/Servo Control
- Power Supplies

Ordering Information:

Example: Select the complete part number from the table below -i.e. PM25RSB120 is a 1200V, 25 Ampere Intelligent Power Module.

| Type | Current Rating Amperes | V _{CES} Volts (x 10) |
|------|---------------------------|----------------------------------|
| PM | 25 | 120 |

PM25RSB120FLAT-BASE TYPE
INSULATED PACKAGE**Absolute Maximum Ratings, $T_j = 25^\circ\text{C}$ unless otherwise specified**

| Ratings | Symbol | PM25RSB120 | Units |
|--|------------------------|-------------|------------------|
| Power Device Junction Temperature | T_j | -20 to 150 | $^\circ\text{C}$ |
| Storage Temperature | T_{stg} | -40 to 125 | $^\circ\text{C}$ |
| Case Operating Temperature | T_C | -20 to 100 | $^\circ\text{C}$ |
| Mounting Torque, M4 Mounting Screws | — | 0.98 ~ 1.47 | N · m |
| Module Weight (Typical) | — | 330 | Grams |
| Supply Voltage Protected by OC and SC ($V_D = 13.5 - 16.5\text{V}$, Inverter Part, $T_j = 125^\circ\text{C}$) | $V_{\text{CC(prot.)}}$ | 800 | Volts |
| Isolation Voltage (Main Terminal to Baseplate, AC 1 min.) | V_{iso} | 2500 | Vrms |

Control Sector

| | | | |
|--|------------------|----|-------|
| Supply Voltage (Applied between $V_{\text{UP1}}-V_{\text{UPC}}$, $V_{\text{VP1}}-V_{\text{VPC}}$, $V_{\text{WP1}}-V_{\text{WPC}}$, $V_{\text{N1}}-V_{\text{NC}}$) | V_D | 20 | Volts |
| Input Voltage (Applied between U_P-V_{UPC} , V_P-V_{VPC} , W_P-V_{WPC} , $U_N \cdot V_N \cdot W_N \cdot B_r-V_{\text{NC}}$) | V_{CIN} | 20 | Volts |
| Fault Output Supply Voltage Applied between ($U_{\text{FO}}-V_{\text{UPC}}$, $V_{\text{FO}}-V_{\text{VPC}}$, $W_{\text{FO}}-V_{\text{WPC}}$, F_O-V_{NC}) | V_{FO} | 20 | Volts |
| Fault Output Current (Sink Current at U_{FO} , V_{FO} , W_{FO} and F_O Terminal) | I_{FO} | 20 | mA |

IGBT Inverter Sector

| | | | |
|--|------------------------|------|---------|
| Collector-Emitter Voltage ($V_D = 15\text{V}$, $V_{\text{CIN}} = 15\text{V}$) | V_{CES} | 1200 | Volts |
| Collector Current, ($T_C = 25^\circ\text{C}$) | I_C | 25 | Amperes |
| Peak Collector Current, ($T_C = 25^\circ\text{C}$) | I_{CP} | 50 | Amperes |
| Supply Voltage (Applied between P - N) | V_{CC} | 900 | Volts |
| Supply Voltage, Surge (Applied between P - N) | $V_{\text{CC(surge)}}$ | 1000 | Volts |
| Collector Dissipation | P_C | 132 | Watts |

Brake Sector

| | | | |
|--|------------------------|------|---------|
| Collector-Emitter Voltage | V_{CES} | 1200 | Volts |
| Collector Current, ($T_C = 25^\circ\text{C}$) | I_C | 10 | Amperes |
| Peak Collector Current, ($T_C = 25^\circ\text{C}$) | I_{CP} | 20 | Amperes |
| Supply Voltage (Applied between P - N) | V_{CC} | 900 | Volts |
| Supply Voltage, Surge (Applied between P - N) | $V_{\text{CC(surge)}}$ | 1000 | Volts |
| Collector Dissipation | P_C | 62 | Watts |
| Diode Forward Current | I_F | 10 | Amperes |
| Diode DC Reverse Voltage | $V_{\text{R(DC)}}$ | 1200 | Volts |

PM25RSB120

FLAT-BASE TYPE
INSULATED PACKAGE

Electrical and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

| Characteristics | Symbol | Test Conditions | Min. | Typ. | Max. | Units |
|---|----------------------|--|------|------|------|------------------|
| Control Sector | | | | | | |
| Over Current Trip Level Inverter Part | OC | $-20^\circ\text{C} \leq T \leq 125^\circ\text{C}$, $V_D = 15\text{V}$ | 32 | 62 | — | Amperes |
| Over Current Trip Level Brake Part | | | 15 | 30 | — | Amperes |
| Short Circuit Trip Level Inverter Part | SC | $-20^\circ\text{C} \leq T \leq 125^\circ\text{C}$, $V_D = 15\text{V}$ | — | 101 | — | Amperes |
| Short Circuit Trip Level Brake Part | | | — | 41 | — | Amperes |
| Over Current Delay Time | $t_{\text{off(OC)}}$ | $V_D = 15\text{V}$ | — | 10 | — | μs |
| Over Temperature Protection | OT | Trip Level | 111 | 118 | 125 | $^\circ\text{C}$ |
| | OT_r | Reset Level | — | 100 | — | $^\circ\text{C}$ |
| Supply Circuit Under Voltage Protection | UV | Trip Level | 11.5 | 12.0 | 12.5 | Volts |
| | UV_r | Reset Level | — | 12.5 | — | Volts |
| Supply Voltage | V_D | Applied between $V_{\text{UP1}}-V_{\text{UPC}}$, $V_{\text{VP1}}-V_{\text{VPC}}$, $V_{\text{WP1}}-V_{\text{WPC}}$, $V_{\text{N1}}-V_{\text{NC}}$ | 13.5 | 15 | 16.5 | Volts |
| Circuit Current | I_D | $V_D = 15\text{V}$, $V_{\text{CIN}} = 15\text{V}$, $V_{\text{N1}}-V_{\text{NC}}$ | — | 44 | 60 | mA |
| | | $V_D = 15\text{V}$, $V_{\text{CIN}} = 15\text{V}$, $V_{\text{XP1}}-V_{\text{XPC}}$ | — | 13 | 18 | mA |
| Input ON Threshold Voltage | $V_{\text{th(on)}}$ | Applied between | 1.2 | 1.5 | 1.8 | Volts |
| Input OFF Threshold Voltage | $V_{\text{th(off)}}$ | U_P-V_{UPC} , V_P-V_{VPC} , W_P-V_{WPC} , $U_N \cdot V_N \cdot W_N \cdot B_r-V_{\text{NC}}$ | 1.7 | 2.0 | 2.3 | Volts |
| PWM Input Frequency | f_{PWM} | 3- ϕ Sinusoidal | — | 15 | 20 | kHz |
| Fault Output Current | $I_{\text{FO(H)}}$ | $V_D = 15\text{V}$, $V_{\text{FO}} = 15\text{V}$ | — | — | 0.01 | mA |
| | $I_{\text{FO(L)}}$ | $V_D = 15\text{V}$, $V_{\text{FO}} = 15\text{V}$ | — | 10 | 15 | mA |
| Minimum Fault Output Pulse Width | t_{FO} | $V_D = 15\text{V}$ | 1.0 | 1.8 | — | ms |

Electrical and Mechanical Characteristics, $T_j = 25^\circ\text{C}$ unless otherwise specified

| Characteristics | Symbol | Test Conditions | Min. | Typ. | Max. | Units |
|--------------------------------------|---------------|---|------|------|------|---------------|
| IGBT Inverter Sector | | | | | | |
| Collector Cutoff Current | I_{CES} | $V_{CE} = V_{CES}, T_j = 25^\circ\text{C}$ | — | — | 1.0 | mA |
| | | $V_{CE} = V_{CES}, T_j = 125^\circ\text{C}$ | — | — | 10 | mA |
| Emitter-Collector Voltage | V_{EC} | $-I_C = 25\text{A}, V_D = 15\text{V}, V_{CIN} = 5\text{V}$ | — | 2.5 | 3.5 | Volts |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $V_D = 15\text{V}, V_{CIN} = 0\text{V}, I_C = 25\text{A}$ | — | 2.5 | 3.5 | Volts |
| | | $V_D = 15\text{V}, V_{CIN} = 0\text{V}, I_C = 25\text{A},$ $T_j = 125^\circ\text{C}$ | — | 2.2 | 3.2 | Volts |
| Inductive Load Switching Times | t_{on} | | 0.5 | 1.0 | 2.5 | μs |
| | t_{rr} | $V_D = 15\text{V}, V_{CIN} = 0 \leftrightarrow 15\text{V}$ | — | 0.15 | 0.3 | μs |
| | $t_{C(on)}$ | $V_{CC} = 600\text{V}, I_C = 25\text{A}$ | — | 0.4 | 1.0 | μs |
| | t_{off} | $T_j = 125^\circ\text{C}$ | — | 2.0 | 3.0 | μs |
| | $t_{C(off)}$ | | — | 0.7 | 1.2 | μs |
| Brake Sector | | | | | | |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $V_D = 15\text{V}, V_{CIN} = 0\text{V}, I_C = 10\text{A},$ $T_j = 25^\circ\text{C}$ | — | 2.8 | 3.8 | Volts |
| | | $V_D = 15\text{V}, V_{CIN} = 0\text{V}, I_C = 10\text{A},$ $T_j = 125^\circ\text{C}$ | — | 2.5 | 3.5 | Volts |
| Diode Forward Voltage | V_{FM} | $-I_C = 10\text{A}, V_D = 15\text{V}, V_{CIN} = 5\text{V}$ | — | 2.5 | 3.5 | Volts |
| Collector Cutoff Current | I_{CES} | $V_{CE} = V_{CES}, T_j = 25^\circ\text{C}$ | — | — | 1 | mA |
| | | $V_{CE} = V_{CES}, T_j = 125^\circ\text{C}$ | — | — | 10 | mA |

PM25RSB120

FLAT-BASE TYPE
INSULATED PACKAGE

Thermal Characteristics

| Characteristic | Symbol | Condition | Min. | Typ. | Max. | Units |
|-------------------------------------|----------------|---|------|------|-------|---------|
| Junction to Case Thermal Resistance | $R_{th(j-c)Q}$ | Each Inverter IGBT | — | — | 0.95 | °C/Watt |
| | $R_{th(j-c)F}$ | Each Inverter FWDi | — | — | 2.5 | °C/Watt |
| | $R_{th(c-f)Q}$ | Each Brake IGBT | — | — | 2.0 | °C/Watt |
| | $R_{th(c-f)F}$ | Each Brake FWDi | — | — | 2.5 | °C/Watt |
| Contact Thermal Resistance | $R_{th(c-f)}$ | Case to Fin Per Module, Thermal Grease Applied | — | — | 0.036 | °C/Watt |










Recommended Conditions for Use

| Characteristic | Symbol | Condition | Value | Units |
|---------------------|----------------|--|----------------|---------|
| Supply Voltage | V_{CC} | Applied across P-N Terminals | 0 ~ 800 | Volts |
| | V_D | Applied between V_{UP1} - V_{UPC} , V_{N1} - V_{NC} , V_{VP1} - V_{VPC} , V_{WP1} - V_{WPC} | 15 ± 1.5 | Volts |
| Input ON Voltage | $V_{CIN(on)}$ | Applied between | 0 ~ 0.8 | Volts |
| Input OFF Voltage | $V_{CIN(off)}$ | U_P , V_P , W_P , U_N , V_N , W_N , B_r | $4.0 \sim V_D$ | Volts |
| PWM Input Frequency | f_{PWM} | Using Application Circuit | 5 ~ 20 | kHz |
| Minimum Dead Time | t_{dead} | Input Signal | ≥ 2.5 | μs |

PM25RSB120

FLAT-BASE TYPE
INSULATED PACKAGE

Inverter Part




PM25RSB120


FLAT-BASE TYPE
INSULATED PACKAGE

Inverter Part


FAULT OUTPUT PULSE WIDTH VS. TEMPERATURE (TYPICAL)




CONTROL SUPPLY VOLTAGE TRIP-RESET LEVEL TEMPERATURE DEPENDENCY (TYPICAL)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (Each IGBT)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (Each FWD)




PM25RSB120


FLAT-BASE TYPE
INSULATED PACKAGE

Brake Part


SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)




COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)




OUTPUT CHARACTERISTICS (TYPICAL)



DIODE FORWARD CHARACTERISTICS



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (Each IGBT)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS (Each FWD)

