



AXIAL SILASTIC GUARD JUNCTION STANDARD RECTIFIER

RL201 THRU RL207

**VOLTAGE RANGE
CURRENT**


**50 to 1000 Volts
2.0 Amperes**

FEATURES

- Low coat construction
- Low forward voltage drop
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:
260°C/10 secods/.375”(9.5mm)lead length at 5 lbs(2.3kg) tension

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.014 ounce, 0.39 grams



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

| | SYMBOLS | RL201 | RL202 | RL203 | RL204 | RL205 | RL206 | RL207 | UNIT |
|---|---------------------------|-------------|-------|-------|-------|-------|-------|-------|---------------------------|
| Maximum Repetitive Peak Reverse Voltage | V_{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | Volts |
| Maximum RMS Voltage | V_{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | Volts |
| Maximum DC Blocking Voltage | V_{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | Volts |
| Maximum Average Forward Rectified Current 0.375”(9.5mm) lead length at $T_A=50^\circ\text{C}$ | $I_{(AV)}$ | 2.0 | | | | | | | Amps |
| Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC method) | I_{FSM} | 30 | | | | | | | Amps |
| Maximum Instantaneous Forward Voltage @2.0A | V_F | 1.0 | | | | | | | Volts |
| Maximum DC Reverse Current at Rated DC Blocking Voltage per element | $T_A = 25^\circ\text{C}$ | 5.0 | | | | | | | μA |
| | $T_A = 100^\circ\text{C}$ | 50 | | | | | | | |
| Maximum Full Load Reverse Current, full cycle average 0.375”(9.5mm)lead length at $T_I=75^\circ\text{C}$ | $I_{R(AV)}$ | 30 | | | | | | | μA |
| Typical Junction Capacitance (Note 1) | C_J | 20 | | | | | | | pF |
| Typical Thermal Resistance (Note 2) | $R_{\theta JA}$ | 40 | | | | | | | $^\circ\text{C}/\text{W}$ |
| Operating Junction Temperature Range | T_J | -55 to +150 | | | | | | | $^\circ\text{C}$ |
| Storage Temperature Range | T_{STG} | -55 to +150 | | | | | | | $^\circ\text{C}$ |

Notes:

1. Measured at 1.0MHz and Applied Reverse Voltage of 4.0V DC.
2. Thermal Resistance from junction to Ambient at .375”(9.5mm)lead length, P.C.board mounted.



AXIAL SILASTIC GUARD JUNCTION STANDARD RECTIFIER

RL201 THRU RL207

VOLTAGE RANGE
CURRENT

50 to 1000 Volts
2.0 Amperes

RATING AND CHARACTERISTIC CURVES RL201 Thru RL207

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

