

SIXF SERIES

SURFACE MOUNT GENERAL PURPOSE RECTIFIERS

产

品

规

格

确

认

书

S1AF THRU S1MF

SURFACE MOUNT GENERAL PURPOSE RECTIFIERS

REVERSE VOLTAGE: 50 to 1000 VOLTS

FORWARD CURRENT: 1.0 AMPERE

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- For surface mounted applications
- Low profile package
- Easy pick and place
- Built-in strain relief
- Low forward voltage drop
- High temperature soldering : 250°C / 10 seconds at terminals


MECHANICAL DATA

Case: Molded plastic, SMAF

Terminals: Solder plated, solderable per MIL-STD-750, method 2026 guaranteed

Polarity: Color band denotes cathode end

Packaging: 12mm tape per EIA STD RS-481



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	S1AF	S1BF	S1DF	S1GF	S1JF	S1KF	S1MF	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current	$I_{(AV)}$	1.0							Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	25							Amp
Maximum Forward Voltage at 1.0A	V_F	1.1							Volts
Maximum Reverse Current at Rated DC Blocking Voltage	I_R	at $T_A=25^\circ\text{C}$							μAmp
		$T_A=125^\circ\text{C}$							
Typical Junction Capacitance (Note 1)	C_J	7							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	83							°C/W
Operating Junction Temperature Range	T_J	-55 to +150							°C
Storage Temperature Range	T_{stg}	-55 to +150							°C

NOTES:

1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

2- Thermal resistance from junction to ambient mounted on P.C.B. with 0.3 x 0.3" (8.0 x 8.0mm) copper pad areas

S1AF THRU S1MF

SURFACE MOUNT GENERAL PURPOSE RECTIFIERS

RATINGS AND CHARACTERISTIC CURVES

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics

