

SCHOTTKY BARRIER RECTIFIERS

REVERSE VOLTAGE - 20 to 200Volts
FORWARD CURRENT - 2.0 Amperes


FEATURES

- Metal-Semiconductor junction with guard ring
- Epitaxial construction
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0
- For use in low voltage,high frequency inverters,free wheeling,and polarity protection applications

MECHANICAL DATA

- Case : JEDEC DO-41 molded plastic
- Polarity : Color band denotes cathode
- Weight : 0.318grams
- Mounting position : Any

DO-41



DO-41		
Dim.	Min.	Max.
A	25.4	-
B	4.20	5.20
C	0.70 \varnothing	0.90 \varnothing
D	2.00 \varnothing	2.70 \varnothing

All Dimensions in millimeter

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

PARAMETER	SYMBOL	SB 220	SB 230	SB 240	SB 250	SB 260	SB 280	SB 2100	SB 2150	SB 2200	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	50	60	80	100	150	200	V
Maximum RMS voltage	V_{RMS}	14	21	28	35	42	56	70	105	140	V
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	80	100	150	200	V
Maximum average forward rectified current	I_F	2.0									A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	50.0									A
Maximum Instantaneous Forward Voltage @ 2.0A	V_F	0.50		0.70		0.85		0.87		0.90	V
Maximum DC Reverse Current @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=100^\circ\text{C}$	I_R	0.5				0.2				mA	
		10.0				5.0					
Typical Junction Capacitance	C_J	150		110		80		70		pF	
Typical Thermal Resistance	$R_{\theta JA}$	60									$^\circ\text{C/W}$
Operating Temperature Range	T_J	-55 to +125					-55 to +150				$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150					-55 to +150				$^\circ\text{C}$

FIG. 1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2-TYPICAL FORWARD CHARACTERISTICS




FIG. 3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE

