


1N4001 thru 1N4007

■ Features

- Low reverse leakage
- High forward surge capability



■ Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	1N4001	1N4002	1N4003	1N4004	1N4005	1N4006	1N4007	Unit
Peak Repetitive Reverse Voltage	V _{RRM}								
Working Peak Reverse Voltage	V _{RMWM}	50	100	200	400	600	800	1000	V
DC Blocking Voltage	V _R								
RMS Reverse Voltage	V _{R(RMS)}	35	70	140	280	420	560	700	V
Average Rectified Output Current	I _O				1.0				A
Non-Repetitive Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}				30				A
DC Blocking Voltage TA = 25°C TA = 100°C	I _{RM}				5				µ A
					50				
Forward Voltage @ I _F = 1.0A	V _{FM}				1.1				V
Typical Junction Capacitance	C _J				15				pF
Typical Thermal Resistance Junction to Ambient	R _{θ JA}				100				K/W
Maximum DC Blocking Voltage Temperature	T _A				+150				°C
Operating and Storage Temperature Range	T _{j, T_{STG}}				-65 to 175				°C