


Plastic Silicon Rectifier



Features

- High efficiency
- High current capability
- High reliability
- High surge current capability
- Low power loss
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Mechanical Data

- **Package:** DO-204AL(DO-41)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes cathode end

■Maximum Ratings (Ta=25 °C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	1N4001G	1N4002G	1N4003G	1N4004G	1N4005G	1N4006G	1N4007G
Device marking code			1N4001G	1N4002G	1N4003G	1N4004G	1N4005G	1N4006G	1N4007G
Repetitive Peak Reverse Voltage	V _{RRM}	V	50	100	200	400	600	800	1000
Average Forward Current @60Hz sine wave, Resistance load, Ta =85 °C	I _{F(AV)}	A	1.0						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Ta=25 °C	I _{FSM}	A	30						
Storage Temperature	T _{stg}	°C	-55 ~+150						
Junction Temperature	T _j	°C	-55~+150						

■Electrical Characteristics (Ta=25 °C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	1N4001G	1N4002G	1N4003G	1N4004G	1N4005G	1N4006G	1N4007G
Maximum instantaneous forward voltage drop per diode	V _{FM}	V	I _{FM} =1.0A	1.1						
Maximum DC reverse current at rated DC blocking voltage per diode	I _{RRM1}	µA	T _a =25 °C	2.5						
	I _{RRM2}		T _a =100 °C	50						
Typical junction capacitance	C _j	pF	Measured at 1MHZ and Applied Reverse Voltage of 4.0 V.D.C.	8						

■Thermal Characteristics (Ta=25 °C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	1N4001G	1N4002G	1N4003G	1N4004G	1N4005G	1N4006G	1N4007G
Thermal Resistance(Typical)	R _{θJ-A}	°C/W	60						

Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
1N4001G~1N4007G	D1	Approximate 0.27	Approximate 3000	3000	30000	Tape

Characteristics (Typical)

FIG.1: I_o-T_a Curve




FIG.2: Forward Surge Current Capability




FIG.3: Forward Voltage






FIG.4: Typical Reverse Characteristics



■ Outline Dimensions



DO-204AL(DO-41)		
Dim	Min	Max
A	4.22	5.21
B	2.03	2.72
C	25.4	/
D	0.69	0.86