



DATA SHEET

SEMICONDUCTOR

1N5221B~1N5281B

500 mW DO-35 Hermetically Sealed Glass Zener Voltage Regulators



Maximum Ratings (Note 1)

Rating	Symbol	Value	Unit
Maximum Steady State Power Dissipation @ $T_L \leq 75^\circ\text{C}$, Lead Length = 3/8"	P_D	500	mW
Derate Above 75°C		4.0	mW/ $^\circ\text{C}$
Operating and Storage Temperature Range	T_J, T_{stg}	-65 to +200	$^\circ\text{C}$


1. Some part number series have lower JEDEC registered ratings.



AXIAL LEAD
DO35

Specification Features

- Zener Voltage Range = 2.4 V to 200 V
- ESD Rating of Class 3 (>16 KV) per Human Body Model
- DO-35 Package (DO-204AH)
- Double Slug Type Construction
- Metallurgical Bonding




Mechanical Characteristics

- Case** : Double slug type, hermetically sealed glass
Finish : All external surfaces are corrosion resistant and leads are readily solderable.
Polarity : Cathode indicated by polarity band
Mounting: Any

Maximum Lead Temperature for Soldering Purposes
230 $^\circ\text{C}$, 1/16" from the case for 10 seconds

MARKING DIAGRAM




1N52xxB = Device Code

1N5221B~1N5281B

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted. Based on DC measurements at thermal equilibrium; lead length = 3/8"; thermal resistance of heat sink = 30°C/W , $V_F = 1.1\text{ V Max}$ @ $I_F = 200\text{mA}$ for all types)

Symbol	Parameter
V_Z	Reverse Zener Voltage @ I_{ZT}
I_{ZT}	Reverse Zener Current
Z_{ZT}	Maximum Zener Impedance @ I_{ZT}
I_{ZK}	Reverse Zener Current
I_R	Reverse Leakage Current @ V_R
V_R	Reverse Voltage
I_F	Forward Current
V_F	Forward Voltage @ I_F
θ_{VZ}	Maximum Zener Voltage Temperature Coefficient



ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 1.1\text{ V Max}$ @ $I_F = 200\text{mA}$ for all types)

Device (Note 2.)	Device Marking	Zener Voltage (Note 3.)				Zener Impedance (Note 4.)			Leakage Current		θ_{VZ} (Note 5.) (%/°C)
		V_Z (Volts)			@ I_{ZT}	Z_{ZT} @ I_{ZT}	Z_{ZK} @ I_{ZK}		I_R @ V_R		
		Min	Nom	Max	(mA)	(Ω)	(Ω)	(mA)	(μA)	(Volts)	
1N5221B	1N5221B	2.28	2.4	2.52	20	30	1200	0.25	100	1	-0.085
1N5222B	1N5222B	2.375	2.5	2.625	20	30	1250	0.25	100	1	-0.085
1N5223B	1N5223B	2.565	2.7	2.835	20	30	1300	0.25	75	1	-0.08
1N5224B	1N5224B	2.66	2.8	2.94	20	30	1400	0.25	75	1	-0.08
1N5225B	1N5225B	2.85	3	3.15	20	29	1600	0.25	50	1	-0.075
1N5226B	1N5226B	3.135	3.3	3.465	20	28	1600	0.25	25	1	-0.07
1N5227B	1N5227B	3.42	3.6	3.78	20	24	1700	0.25	15	1	-0.065
1N5228B	1N5228B	3.705	3.9	4.095	20	23	1900	0.25	10	1	-0.06
1N5229B	1N5229B	4.085	4.3	4.515	20	22	2000	0.25	5	1	± 0.055
1N5230B	1N5230B	4.465	4.7	4.935	20	19	1900	0.25	5	2	± 0.03
1N5231B	1N5231B	4.845	5.1	5.355	20	17	1600	0.25	5	2	± 0.03
1N5232B	1N5232B	5.32	5.6	5.88	20	11	1600	0.25	5	3	+0.038
1N5233B	1N5233B	5.7	6	6.3	20	7	1600	0.25	5	3.5	+0.038
1N5234B	1N5234B	5.89	6.2	6.51	20	7	1000	0.25	5	4	+0.045
1N5235B	1N5235B	6.46	6.8	7.14	20	5	750	0.25	3	5	+0.05

2. TOLERANCE AND TYPE NUMBER DESIGNATION (V_Z)

The type numbers listed have a standard tolerance on the nominal zener voltage of $\pm 5\%$.

3. ZENER VOLTAGE (V_Z) MEASUREMENT

Nominal zener voltage is measured with the device junction in the thermal equilibrium at the lead temperature (T_L) at $30^\circ\text{C} \pm 1^\circ\text{C}$ and 3/8" lead length.

4. ZENER IMPEDANCE (Z_Z) DERIVATION

Z_{ZT} and Z_{ZK} are measured by dividing the AC voltage drop across the device by the AC current applied. The specified limits are for $I_{Z(AC)} = 0.1 I_{Z(DC)}$ with AC frequency = 60Hz.

5. TEMPERATURE COEFFICIENT (θ_{VZ})

Test conditions for temperature coefficient are as follows:

- A. $I_{ZT} = 7.5\text{mA}$, $T_1 = 25^\circ\text{C}$, $T_2 = 125^\circ\text{C}$ (1N5221B through 1N5242B)
- B. $I_{ZT} = \text{Rated } I_{ZT}$, $T_1 = 25^\circ\text{C}$, $T_2 = 125^\circ\text{C}$ (1N5243B through 1N5281B)

Device to be temperature stabilized with current applied prior to reading breakdown voltage at the specified ambient temperature.

1N5221B~1N5281B

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted, V_F = 1.1 V Max @ I_F = 200mA for all types)

Device (Note 6.)	Device Marking	Zener Voltage (Note 7.)			Zener Impedance (Note 8.)			Leakage Current		θ _{vz} (Note 9.)	
		V _Z (Volts)			@ I _{ZT}	Z _{ZT} @ I _{ZT}	Z _{ZK} @ I _{ZK}	I _R @ V _R			
		Min	Nom	Max	(mA)	(Ω)	(Ω)	(mA)	(μA)	(Volts)	(%/°C)
1N5236B	1N5236B	7.125	7.5	7.875	20	6	500	0.25	3	6	+0.058
1N5237B	1N5237B	7.79	8.2	8.61	20	8	500	0.25	3	6.5	+0.062
1N5238B	1N5238B	8.265	8.7	9.135	20	8	600	0.25	3	6.5	+0.065
1N5239B	1N5239B	8.645	9.1	9.555	20	10	600	0.25	3	7	+0.068
1N5240B	1N5240B	9.5	10	10.5	20	17	600	0.25	3	8	+0.075
1N5241B	1N5241B	10.45	11	11.55	20	22	600	0.25	2	8.4	+0.076
1N5242B	1N5242B	11.4	12	12.6	20	30	600	0.25	1	9.1	+0.077
1N5243B	1N5243B	12.35	13	13.65	9.5	13	600	0.25	0.5	9.9	+0.079
1N5244B	1N5244B	13.3	14	14.7	9	15	600	0.25	0.1	10	+0.082
1N5245B	1N5245B	14.25	15	15.75	8.5	16	600	0.25	0.1	11	+0.082
1N5246B	1N5246B	15.2	16	16.8	7.8	17	600	0.25	0.1	12	+0.083
1N5247B	1N5247B	16.15	17	17.85	7.4	19	600	0.25	0.1	13	+0.084
1N5248B	1N5248B	17.1	18	18.9	7	21	600	0.25	0.1	14	+0.085
1N5249B	1N5249B	18.05	19	19.95	6.6	23	600	0.25	0.1	14	+0.086
1N5250B	1N5250B	19	20	21	6.2	25	600	0.25	0.1	15	+0.086
1N5251B	1N5251B	20.9	22	23.1	5.6	29	600	0.25	0.1	17	+0.087
1N5252B	1N5252B	22.8	24	25.2	5.2	33	600	0.25	0.1	18	+0.088
1N5253B	1N5253B	23.75	25	26.25	5	35	600	0.25	0.1	19	+0.089
1N5254B	1N5254B	25.65	27	28.35	4.6	41	600	0.25	0.1	21	+0.09
1N5255B	1N5255B	26.6	28	29.4	4.5	44	600	0.25	0.1	21	+0.091
1N5256B	1N5256B	28.5	30	31.5	4.2	49	600	0.25	0.1	23	+0.091
1N5257B	1N5257B	31.35	33	34.65	3.8	58	700	0.25	0.1	25	+0.092
1N5258B	1N5258B	34.2	36	37.8	3.4	70	700	0.25	0.1	27	+0.093
1N5259B	1N5259B	37.05	39	40.95	3.2	80	800	0.25	0.1	30	+0.094
1N5260B	1N5260B	40.85	43	45.15	3	93	900	0.25	0.1	33	+0.095
1N5261B	1N5261B	44.65	47	49.35	2.7	105	1000	0.25	0.1	36	+0.095
1N5262B	1N5262B	48.45	51	53.55	2.5	125	1100	0.25	0.1	39	+0.096
1N5263B	1N5263B	53.2	56	58.8	2.2	150	1300	0.25	0.1	43	+0.096
1N5264B	1N5264B	57	60	63	2.1	170	1400	0.25	0.1	46	+0.097
1N5265B	1N5265B	58.9	62	65.1	2	185	1400	0.25	0.1	47	+0.097

6. TOLERANCE AND TYPE NUMBER DESIGNATION (V_Z)

The type numbers listed have a standard tolerance on the nominal zener voltage of ±5%.

7. ZENER VOLTAGE (V_Z) MEASUREMENT

Nominal zener voltage is measured with the device junction in the thermal equilibrium at the lead temperature (T_L) at 30°C ±1°C and 3/8" lead length.

8. ZENER IMPEDANCE (Z_Z) DERIVATION

Z_{ZT} and Z_{ZK} are measured by dividing the AC voltage drop across the device by the AC current applied. The specified limits are for I_{Z(AC)} = 0.1 I_{Z(DC)} with AC frequency = 60Hz.

9. TEMPERATURE COEFFICIENT (θ_{vz})

Test conditions for temperature coefficient are as follows:

A. I_{ZT} = 7.5mA, T₁ = 25°C, T₂ = 125°C (1N5221B through 1N5242B)

B. I_{ZT} = Rated I_{ZT}, T₁ = 25°C, T₂ = 125°C (1N5243B through 1N5281B)

Device to be temperature stabilized with current applied prior to reading breakdown voltage at the specified ambient temperature.

1N5221B~1N5281B

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 1.1\text{ V Max}$ @ $I_F = 200\text{mA}$ for all types)

Device (Note 10.)	Device Marking	Zener Voltage (Note 11.)				Zener Impedance (Note 12.)			Leakage Current		θ_{VZ} (Note 13.)
		V_Z (Volts)			@ I_{ZT}	Z_{ZT} @ I_{ZT}	Z_{ZK} @ I_{ZK}		I_R @ V_R		
		Min	Nom	Max	(mA)	(Ω)	(Ω)	(mA)	(μA)	(Volts)	(%/°C)
1N5266B	1N5266B	64.6	68	71.4	1.8	230	1600	0.25	0.1	52	+0.097
1N5267B	1N5267B	71.25	75	78.75	1.7	270	1700	0.25	0.1	56	+0.098
1N5268B	1N5268B	77.9	82	86.1	1.5	330	2000	0.25	0.1	62	+0.098
1N5269B	1N5269B	82.65	87	91.35	1.4	370	2200	0.25	0.1	68	+0.099
1N5270B	1N5270B	86.45	91	95.55	1.4	400	2300	0.25	0.1	69	+0.099
1N5271B	1N5271B	95	100	105	1.3	500	2600	0.25	0.1	76	+0.11
1N5272B	1N5272B	104.5	110	115.5	1.1	750	3000	0.25	0.1	84	+0.11
1N5273B	1N5273B	114	120	126	1	900	4000	0.25	0.1	91	+0.11
1N5274B	1N5274B	123.5	130	136.5	0.95	1100	4500	0.25	0.1	99	+0.11
1N5275B	1N5275B	133	140	147	0.9	1300	4500	0.25	0.1	106	+0.11
1N5276B	1N5276B	142.5	150	157.5	0.85	1500	5000	0.25	0.1	114	+0.11
1N5277B	1N5277B	152	160	168	0.8	1700	5500	0.25	0.1	122	+0.11
1N5278B	1N5278B	161.5	170	178.5	0.74	1900	5500	0.25	0.1	129	+0.11
1N5279B	1N5279B	171	180	189	0.68	2200	6000	0.25	0.1	137	+0.11
1N5280B	1N5280B	180.5	190	199.5	0.66	2400	6500	0.25	0.1	144	+0.11
1N5281B	1N5281B	190	200	210	0.65	2500	7000	0.25	0.1	152	+0.11

10. TOLERANCE AND TYPE NUMBER DESIGNATION (V_Z)

The type numbers listed have a standard tolerance on the nominal zener voltage of $\pm 5\%$.

11. ZENER VOLTAGE (V_Z) MEASUREMENT

Nominal zener voltage is measured with the device junction in the thermal equilibrium at the lead temperature (T_L) at $30^\circ\text{C} \pm 1^\circ\text{C}$ and 3/8" lead length.

12. ZENER IMPEDANCE (Z_Z) DERIVATION

Z_{ZT} and Z_{ZK} are measured by dividing the AC voltage drop across the device by the AC current applied. The specified limits are for $I_{Z(AC)} = 0.1 I_{Z(DC)}$ with AC frequency = 60Hz.

13. TEMPERATURE COEFFICIENT (θ_{VZ})

Test conditions for temperature coefficient are as follows:

- A. $I_{ZT} = 7.5\text{mA}$, $T_1 = 25^\circ\text{C}$, $T_2 = 125^\circ\text{C}$ (1N5221B through 1N5242B)
- B. $I_{ZT} = \text{Rated } I_{ZT}$, $T_1 = 25^\circ\text{C}$, $T_2 = 125^\circ\text{C}$ (1N5243B through 1N5281B)

Device to be temperature stabilized with current applied prior to reading breakdown voltage at the specified ambient temperature.

DEVICE CHARACTERISTICS

1N5221B~1N5281B




Figure 1. Steady State Power Derating




Figure 2. Typical Thermal Resistance




Figure 3. Typical Leakage Current

DEVICE CHARACTERISTICS

1N5221B~1N5281B

TEMPERATURE COEFFICIENTS

(-55°C to +150°C temperature range; 90% of the units are in the ranges indicated.)




Figure 4a. Range for Units to 12 Volts




Figure 4b. Range for Units 12 to 100 Volts




Figure 4c. Range for Units 120 to 200 Volts




Figure 5. Effect of Zener Current




Figure 6a. Typical Capacitance 2.4-100 Volts




Figure 6b. Typical Capacitance 120-200 Volts

DEVICE CHARACTERISTICS

1N5221B~1N5281B




Figure 7a. Maximum Surge Power 1.8-91 Volts




Figure 7b. Maximum Surge Power DO-35 100-200Volts




Figure 8. Effect of Zener Current on Zener Impedance




Figure 9. Effect of Zener Voltage on Zener Impedance




Figure 10. Typical Forward Characteristics

DEVICE CHARACTERISTICS

1N5221B~1N5281B




Figure 1 1. Zener Voltage versus Zener Current - $V_Z = 1$ thru 16 Volts




Figure 12. Zener Voltage versus Zener Current - $V_Z = 15$ thru 30 Volts

DEVICE CHARACTERISTICS

1N5221B~1N5281B




Figure 13. Zener Voltage versus Zener Current - $V_Z = 30$ thru 105 Volts





Figure 14. Zener Voltage versus Zener Current - $V_Z = 110$ thru 220 Volts

PACKAGE OUTLINE & DIMENSIONS

1N5221B~1N5281B

Package Outline

Package	Case Outline				
DO-35					
	DO-35				
	DIM	Millimeters		Inches	
		Min	Max	Min	Max
	A	0.46	0.55	0.018	0.022
B	3.05	5.08	0.120	0.200	
C	25.40	38.10	1.000	1.500	
D	1.53	2.28	0.060	0.090	

Notes:

1. All dimensions are within JEDEC standard.
2. DO35 polarity denoted by cathode band.