


Aerospace 40 V power Schottky rectifier

Features

- Aerospace applications
- Surface mount hermetic package
- High thermal conductivity materials
- Very small conduction losses
- Negligible switching losses
- Extremely fast switching
- Low forward voltage drop
- Supplied against an ST detailed procurement specification
- Package weight: 0.18 g
- Target radiation qualification
 - 150 krad (Si) low dose rate
 - 3 Mrad (Si) high dose rate
- Under ESCC qualification



Description

This power Schottky rectifier is designed and packaged to comply with the ESCC5000 specification for aerospace products. It is housed in a surface mount hermetically sealed LCC2B package whose footprint is 100% compatible with industry standard solutions in D5B.

The 1N5822U is suitable for switching mode power supplies and high frequency DC to DC converters such as low voltage high frequency inverter, free wheeling or polarity protection.

Table 1. Device summary⁽¹⁾

Order code	ESCC detailed specification	Quality level	Lead finish	EPPL	$I_{F(AV)}$	V_{RRM}	$T_{J(max)}$	$V_F(max)$
1N5822UB1	-	Engineering model	Gold plated	-	3 A	40 V	150 °C	0.47 V
1N5822U01B	TBD ⁽²⁾	Flight part	Gold plated	Y				
1N5822U02B	TBD ⁽²⁾	Flight part	Solder dip	Y				

1. Contact ST sales office for information about the specific conditions for products in die form and QML-Q versions.

2. TBD: to be defined upon ESCC qualification

1 Characteristics

Table 2. Absolute ratings (limiting values)

Symbol	Parameter	Value	Unit	
V _{RRM}	Repetitive peak reverse voltage	40	V	
I _{F(RMS)}	Forward rms current	10	A	
I _{F(AV)}	Average forward rectified current	T _c = 135 °C, δ = 0.5	3	A
I _{FSM}	Forward surge current	t _p = 10 ms sinusoidal	80	A
T _{stg}	Storage temperature range	-65 to + 150	°C	
T _j	Maximum operating junction temperature ⁽¹⁾	150	°C	
T _{sol}	Maximum soldering temperature ⁽²⁾	245	°C	

- $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$ condition to avoid thermal runaway for a diode on its own heatsink
- Maximum duration 5 s. The same package must not be resoldered until 3 minutes have elapsed.

Table 3. Thermal resistance

Symbol	Parameter	Value	Unit
R _{th(j-c)}	Junction to case	7	°C/W

Table 4. Static electrical characteristics

Symbol	Parameter	Tests conditions	Min.	Typ.	Max.	Unit	
I _R ⁽¹⁾	Reverse current	T _j = -55 °C	V _R = 40 V	-	-	40	μA
		T _j = 25 °C		-	-	80	
		T _j = 100 °C		-	-	12	mA
V _F ⁽²⁾	Forward voltage	T _j = 25 °C	I _F = 1 A	-	-	0.4	V
		T _j = -55 °C	I _F = 3 A	-	-	0.56	
		T _j = 25 °C		-	-	0.485	
		T _j = 100 °C		-	-	0.455	
		T _j = 25 °C	I _F = 9.4 A	-	-	0.70	

- Pulse test : t_p = 5 ms, δ < 2%
- Pulse test : t_p = 680 μs, δ < 2%

To evaluate the conduction losses use the following equation:

$$P = 0.32 \times I_{F(AV)} + 0.050 I_{F(RMS)}^2$$

Table 5. Dynamic characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C _j	Diode capacitance	V _R = 5 V, F = 1 MHz	-	-	240	pF

Figure 1. Average forward power dissipation versus average forward current




Figure 2. Average forward current versus ambient temperature (delta = 0.5)




Figure 3. Non repetitive surge peak forward current versus overload duration (maximum values)




Figure 4. Relative variation of thermal impedance junction to case versus pulse duration




Figure 5. Reverse leakage current versus reverse voltage applied (typical values)




Figure 6. Forward voltage drop versus forward current (typical values)





Figure 7. Non repetitive surge peak forward current versus number of cycles



2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

Table 6. Leadless chip carrier 2 (LCC2B) package dimensions

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A ⁽¹⁾	2.04	2.23	2.42	0.080	0.088	0.095
B	5.27	5.4	5.6	0.207	0.213	0.220
C	3.49	3.62	3.82	0.137	0.143	0.150
D	1.71	1.90	2.09	0.067	0.075	0.082
E	0.48	-	0.71	0.019	-	0.028
F	-	1.4	-	-	0.055	-
G	-	3.32	-	-	0.131	-
H	-	1.82	-	-	0.072	-
I	-	0.15	-	-	0.006	-
r1	-	0.15	-	-	0.006	-
r2	-	0.20	-	-	0.008	-

Note 1: The anode is identified by metallization in two top internal angles and the index mark.

1. Measurement prior to solder coating the mounting pads on bottom of package

3 Ordering information

Table 7. Ordering information⁽¹⁾

Order code	ESCC detailed specification	Package	Lead finish	Marking	EPPL	Weight	Packing
1N5822UB1	-	LCC2B	Gold plated	22UB1	-	0.18 g	Waffle pack
1N5822U01B	TBD ⁽²⁾		Gold plated	22U01B	Y	0.18 g	
1N5822U02B	TBD ⁽²⁾		Solder dip	22U02B	Y		

1. Contact ST sales office for information about the specific conditions for products in die form and QML-Q versions.

2. TBD: to be defined upon ESCC qualification

4 Revision history

Table 8. Document revision history

Date	Revision	Changes
10-Aug-2009	1	First issue.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com