

20 STERN AVE.
 SPRINGFIELD, NEW JERSEY 07081
 U.S.A.

TELEPHONE: (973) 376-2922
 (212) 227-6005
 FAX: (973) 376-8960

MAXIMUM RATINGS

Operating Temperature: -65°C to +175°C
 Storage Temperature: -65°C to +175°C
 Power Dissipation: 500 mW @ $T_L = +75^\circ\text{C}$ @ $L = 3/8"$
 Power Derating: 5mW/°C above $T_L = +75^\circ\text{C}$
 Forward Voltage: 1.4V dc @ $I_F = 1\text{A}$ dc (Pulsed)


**1N6309
 THRU
 1N6320**

- 500 mW ZENER DIODES
- NON CAVITY CONSTRUCTION
- METALLURGICALLY BONDED

ELECTRICAL CHARACTERISTICS @ 25°C, unless otherwise specified

TYPE	V _{Z2} NOM. ±5% @ I _{Z2}	V _{Z1} MIN. @ I _{Z1} 250μA	I _{Z2} TEST CURRENT	Z _Z @ I _{Z2}	Z _{ZK} @ 250μA	I _{ZM}	V _Z (reg) Δ V _Z (1)	I _{ZSM} SURGE	V _R	I _{R1} @ 25°C	I _{R2} @ TA= 150°C	N _D @ 250 μA 1-3 kHz
	VOLTS	VOLTS	mA	OHMS	OHMS	mA	VOLTS	AMPS	VOLTS	μA	μA	μV/√Hz
1N6309	2.4	1.1	20	30	1200	177	1.5	2.5	1.0	100	200	1.0
1N6310	2.7	1.2	20	30	1300	157	1.5	2.2	1.0	60	150	1.0
1N6311	3.0	1.3	20	29	1400	141	1.5	2.0	1.0	30	100	1.0
1N6312	3.3	1.5	20	24	1400	128	1.6	1.8	1.0	5.0	20	1.0
1N6313	3.6	1.8	20	22	1400	117	1.6	1.65	1.0	3.0	12	1.0
1N6314	3.9	2.0	20	20	1700	108	1.6	1.5	1.0	2.0	12	1.0
1N6315	4.3	2.4	20	18	1400	99	0.9	1.4	1.0	2.0	12	1.0
1N6316	4.7	2.8	20	16	1500	90	0.5	1.27	1.5	5.0	12	1.0
1N6317	5.1	3.3	20	14	1300	83	0.4	1.17	2.0	5.0	12	1.0
1N6318	5.6	4.3	20	8.0	1200	76	0.4	1.10	2.5	5.0	10	2.0
1N6319	6.2	5.2	20	3.0	800	68	0.3	0.97	3.5	5.0	10	5.0
1N6320	6.8	6.0	20	3.0	400	63	0.35	1.23	4.0	2.0	50	5.0

NOTE 1 Δ V_Z = V_Z @ 20 mAdc minus V_Z @ 2 mAdc



DESIGN DATA

CASE: Hermetically sealed, Glass "D"

LEAD MATERIAL: Copper clad steel


LEAD FINISH: Tin / Lead

THERMAL RESISTANCE: (R_{ΘJL}): 250 °C/W maximum

THERMAL IMPEDANCE: (Z_{ΘJX}): 15 °C/W maximum

POLARITY: Diode to be operated with the banded (cathode) end positive.

MOUNTING POSITION: Any



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.