

Olitech Electronics Co. Ltd

Email: info@olitech-elec.com Website: www.olitech-elec.com

Plastic-Encapsulate Diodes


HIGH SPEED SWITCHING DIODE

1SS400

FEATURES

- Small surface mounting type
- High Speed
- High reliability with high surge current handing capability

MARKING: A



Maximum Ratings and Electrical Characteristics, Single Diode @TA=25 °C

Parameter	Symbol	Limits	Unit
Peak reverse voltage	V _R	90	V
DC reverse voltage	V _R	80	V
Peak forward current	I _F	225	mA
Mean rectifying current	I _O	100	mA
Surge current (1s)	I _{surge}	500	mA
Junction temperature	T _j	125	°C
Storage temperature	T _{stg}	-55~+125	°C

ELECTRICAL CHARACTERISTICS (T_{amb}=25 °C unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V _F			1.2	V	I _F =100mA
Reverse current	I _R			0.1	μA	V _R =80V
Capacitance between terminals	C _T			3.0	pF	V _R =0.5V, f=1MHZ
Reverse recovery time	t _{rr}			4	ns	V _R =6V, I _F =10mA, R _L =100

1SS400 Typical Characteristics




Fig.1 Forward characteristics




Fig.2 Reverse characteristics




Fig.3 Capacitance between terminals




Fig.4 Reverse recovery time characteristics




Fig.5 Surge current characteristics