


New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.
SPRINGFIELD, NEW JERSEY 07081
U.S.A.

TELEPHONE: (973) 376-2922
(212) 227-6005
FAX: (973) 376-8960


2N3439; 2N3440; 2N4063; 2N4064; 40385; 40346, V1, V2; 40390; 40412, V1, V2 High-Voltage Silicon N-P-N Transistors

	2N3439	2N3440	40346	40412	
	2N4063	2N4064	40346V1	40412V1	
	40385	40390	40346V2	40412V2	
MAXIMUM RATINGS, Absolute-Maximum Values:					
*COLLECTOR-TO-BASE VOLTAGE V_{CB0}	450	300	—	—	V
COLLECTOR-TO-EMITTER VOLTAGE:					
With external base-to-emitter resistance					
(R_{BE}) = 1,000 Ω $V_{CER(sus)}$	—	—	175	—	V
= 10,000 Ω $V_{CER(sus)}$	—	—	—	250	V
* With base open $V_{CEO(sus)}$	350	250	—	—	V
*EMITTER-TO-BASE VOLTAGE V_{EBO}	7	7	—	—	V
*CONTINUOUS COLLECTOR CURRENT I_C	1	1	1	1	A
*CONTINUOUS BASE CURRENT I_B	0.5	0.5	0.5	0.5	A
TRANSISTOR DISSIPATION: P_T					
At case temperature up to 25°C	10	10(2N3440)	10(40346)	10(40412)	W
At free-air temperatures up to 25°C	1(40385)	10(2N4064)	10(40346V2)	10(40412V2)	W
At free-air temperatures up to 50°C	1(2N3439)	3.5(40390)	4(40346V1)	4(40412V1)	W
At free-air temperatures above 25°C or 50°C		1(2N3440)	1(40346)	1(40412)	W
		Derate linearly to 200°C			°C
*TEMPERATURE RANGE:					
Storage & Operating (Junction)	—65 to 200			°C	
*LEAD TEMPERATURE (During soldering):					
At distances \geq 1/32 in (0.79 mm)	—			°C	
from seating plane for 10 s max.	—255			°C	



JEDEC TO-39 with Flange
2N4063, 2N4064, 40346V2,
40412V2

*2N-Series types in accordance with JEDEC registration data
NOTE: P_T value of 10 W at $T_C = 25^\circ\text{C}$ and lead temperature of 265°C are registered data for 2N4063 and 2N4064 only.



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

Quality Semi-Conductors

**2N3439; 2N3440; 2N4063; 2N4064; 40385;
40346, V1, V2; 40390; 40412, V1, V2**

ELECTRICAL CHARACTERISTICS, Case Temperature (T_C) = 25°C, Unless Otherwise Specified

CHARACTERISTICS	SYMBOL	VOLTAGE		CURRENT	LIMITS								UNITS
		V dc			mA dc	2N3439 2N4063 40385		2N3440 2N4064 40390		40346 40346V1 40346V2		40412 40412V1 40412V2	
		V_{CE}	V_{BE}	I_C		MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	
Collector-Cutoff Current: With base open	I_{CEO}	100 200 300	—		—	—	—	—	—	5	—	5	μA
With base reverse-biased:	I_{CEV}	200 300 450	— 1.5 — 1.5 — 1.5		—	—	—	—	—	10	—	—	
At $T_C = 150^\circ C$		150 200	— 1.5 — 1.5		—	—	—	—	—	—	—	2	mA
With $R = 10,000$ ohms	I_{CER}	100			—	—	—	—	—	—	—	1	mA
Emitter-Cutoff Current	I_{EBO}		— 3 — 4 — 6		—	—	—	—	—	—	—	100	μA
DC Forward-Current Transfer Ratio	h_{FE}	10 10 10 20		2 10 20 30	30 — 40 —	— — 160 —	— — 40 —	— — 160 —	— — — —	— — — —	— — — 40	—	
Collector-to-Emitter Sustaining Voltage: With base open	$V_{CEO(sus)}$			50	350 ^a	—	250 ^a	—	—	—	—	—	V
Collector-to-Emitter Sustaining Voltage: With external base-to- emitter resistance $R_{BE} = 1,000$ ohms $R_{BE} = 10,000$ ohms	$V_{CER(sus)}$ $V_{CER(sus)}$			50 50	— —	— —	— —	— —	175 ^a —	— —	— 250 ^a	— —	V
Base-to-Emitter Voltage	V_{BE}	10		10	—	—	—	—	—	1	—	—	V
Base-to-Emitter Saturation Voltage $I_B = 4$ mA	$V_{BE(sat)}$			50	—	1.3	—	1.3	—	—	—	—	V
Collector-to-Emitter Saturation Voltage $I_B = 1$ mA $I_B = 4$ mA	$V_{CE(sat)}$			10 50	— —	— 0.5	— —	— 0.5	— —	0.5 —	— —	0.5 —	V
Small-Signal Forward- Current Transfer Ratio: $f = 5$ MHz	h_{fe}	10		10	3	—	3	—	2	—	2	—	
Output Capacitance: $V_{CB} = 10$ V, $f = 1$ MHz	C_{ob}				—	10	—	10	—	10	—	10	pF
Second-Breakdown Current	$I_{S/b}$	200			—	—	—	—	—	—	50	—	mA
Thermal Resistance: Junction-to-case	$R_{\theta JC}$				—	17.5	—	17.5	15 max. (40346) (40346V2)	15 max. (40412) (40412V2)			$^\circ C/W$
Junction-to-free air	$R_{\theta JFA}$				—	—	—	—	45 max. (40346V1)	45 max. (40412V1)			

^a2N-Series types in accordance with JEDEC registration data

^bCAUTION: The sustaining voltages, $V_{CEO(sus)}$ and $V_{CER(sus)}$, MUST NOT be measured on a curve tracer