

Silicon PNP Power Transistors

2N6229 2N6230 2N6231

DESCRIPTION

- With TO-3 package
- Low collector saturation voltage
- Excellent safe operating area

APPLICATIONS

- For high power audio; disk head positioners and other linear applications.

PINNING

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector




Fig.1 simplified outline (TO-3) and symbol

Absolute maximum ratings(Ta=□)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	2N6229	-100	V
		2N6230	-120	
		2N6231	-140	
V _{CEO}	Collector-emitter voltage	2N6229	-100	V
		2N6230	-120	
		2N6231	-140	
V _{EBO}	Emitter-base voltage	Open collector	-7	V
I _C	Collector current		-10	A
P _D	Total power dissipation	T _C =25□	150	W
T _j	Junction temperature		150	□
T _{stg}	Storage temperature		-65~200	□

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	VALUE	UNIT
R _{th j-c}	Thermal resistance junction to case	0.875	□/W

Silicon PNP Power Transistors

2N6229 2N6230 2N6231

CHARACTERISTICS

T_j=25 °C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-emitter sustaining voltage	2N6229	I _C =-0.2A ; I _B =0	-100			V
		2N6230		-120			
		2N6231		-140			
V _{CEsat}	Collector-emitter saturation voltage		I _C =-4A; I _B =-0.4A			-1.0	V
V _{BE}	Base-emitter on voltage		I _C =-5A ; V _{CE} =-2V			-2.0	V
I _{CEO}	Collector cut-off current		V _{CE} =Rated V _{CEO} ; I _B =0			-5.0	mA
I _{CBO}	Collector cut-off current		V _{CB} =Rated V _{CBO} ; I _E =0			-1.0	mA
I _{EBO}	Emitter cut-off current		V _{EB} =-7V; I _C =0			-0.1	mA
h _{FE}	DC current gain	2N6229	I _C =-5A ; V _{CE} =-2V	25		100	
		2N6230		20		80	
		2N6231		15		60	
f _T	Transition frequency		I _C =-0.5A ; V _{CE} =-4V	1			MHz

Silicon PNP Power Transistors

2N6229 2N6230 2N6231

PACKAGE OUTLINE



Fig.2 outline dimensions (unindicated tolerance:±0.1mm)