



ON Semiconductor®

**ON Semiconductor**  
**DATA SHEET****2SA1415 / 2SC3645** — PNP / NPN Epitaxial Planar Silicon Transistors  
**High-Voltage Switching,  
Predriver Applications****Features**

- Adoption of FBET process.
- High breakdown voltage ( $V_{CEO}=160V$ ).
- Excellent linearity of  $h_{FE}$  and small  $C_{ob}$ .
- Fast switching speed.
- Ultrasmall size marking it easy to provide high-density, small-sized hybrid ICs.

**Specifications** ( ) : 2SA1415**Absolute Maximum Ratings** at  $T_a=25^{\circ}C$ 

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	$V_{CBO}$		(-)180	V
Collector-to-Emitter Voltage	$V_{CEO}$		(-)160	V
Emitter-to-Base Voltage	$V_{EBO}$		(-)5	V
Collector Current	IC		(-)140	mA
Collector Current (Pulse)	ICP		(-)200	mA
Collector Dissipation	PC		500	mW
		Moutned on ceramic board (250mm <sup>2</sup> ×0.8mm)	1.3	W
Junction Temperature	TJ		150	°C
Storage Temperature	Tstg		-55 to +150	°C

Marking : 2SA1415 : AA, 2SC3645: CA

# 2SA1415 / 2SC3645

## Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = (-)80V, I_E = 0A$			(-)100	nA
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = (-)4V, I_C = 0A$			(-)100	nA
DC Current Gain	$h_{FE}$	$V_{CE} = (-)5V, I_C = (-)10mA$	140*		400*	
Gain-Bandwidth Product	$f_T$	$V_{CE} = (-)10V, I_C = (-)10mA$		150		MHz
Output Capacitance	$C_{ob}$	$V_{CB} = (-)10V, f = 1MHz$		(4.0)3.0		pF
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)50mA, I_B = (-)5mA$		(-0.14)0.07	(-0.4)0.3	V
Turn-ON Time	$t_{on}$	See sepcified Test Circuit.		0.1		μs
Strage Time	$t_{stg}$	See sepcified Test Circuit.		1.5		μs
Fall Time	$t_f$	See sepcified Test Circuit.		0.1		μs


\* : The 2SA1415/2SC3645 are classified by 10mA  $h_{FE}$  as follows :

Rank	S	T
$h_{FE}$	140 to 280	200 to 400


## Package Dimensions

unit : mm (typ)



7007A-004











## Switching Time Test Circuit










$I_C = 10I_{B1} = -10I_{B2} = 10mA$   
For PNP, the polarity is reversed.



2SA1415 / 2SC3645



# 2SA1415 / 2SC3645



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. SCILLC strives to supply high-quality high-reliability products and recommends adopting safety measures when designing equipment to avoid accidents or malfunctions. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals," must be validated for each customer application by customer's technical experts. SCILLC shall not be held liable for any claim or suits with regard to a third party's intellectual property rights which has resulted from the use of the technical information and products mentioned above. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### **PUBLICATION ORDERING INFORMATION**

##### **LITERATURE FULFILLMENT:**

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada.

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative