


PNP General Purpose Transistors

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CEO}	-50	Vdc
Collector-Base Voltage	V_{CBO}	-60	Vdc
Emitter-Base Voltage	V_{EBO}	-6.0	Vdc
Collector Current-Continuous	I_C	-150	mAdc

THERMAL CHARACTERISTICS

Characteristics	Symbol	Max	Unit
Total Device Dissipation FR-5 Board (1) $T_A=25^{\circ}\text{C}$ Derate above 25°C	P_D	150 1.2	mW mW/ $^{\circ}\text{C}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	833	$^{\circ}\text{C/W}$
Junction and Storage, Temperature	T_J, T_{stg}	-55 to +150	$^{\circ}\text{C}$

DEVICE MARKING

2SA1774Q=FQ, 2SA1774S=FS, 2SA1774R=FR

ELECTRICAL CHARACTERISTICS

Characteristics	Symbol	Min	Max	Unit
-----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage ($I_C = -1 \mu\text{Adc}, I_B = 0$)	$V_{(BR)CEO}$	-50	-	Vdc
Collector-Base Breakdown Voltage ($I_C = -50 \mu\text{Adc}, I_E = 0$)	$V_{(BR)CBO}$	-60	-	Vdc
Emitter-Base Breakdown Voltage ($I_E = -50 \mu\text{Adc}, I_C = 0$)	$V_{(BR)EBO}$	-6.0	-	Vdc
Collector Cutoff Current ($V_{CE} = -50 \text{Vdc}, I_E = 0$)	I_{CEO}	-	-0.1	μAdc
Collector Cutoff Current ($V_{CB} = -60 \text{Vdc}, I_E = 0$)	I_{CBO}	-	-0.1	μAdc
Emitter Cutoff Current ($V_{EB} = -6.0 \text{Vdc}, I_C = 0$)	I_{EBO}	-	-0.1	μAdc

1.FR-5=1.0 x 0.75 x 0.062 in

2SA1774



ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise noted) (Continued)







Characteristics	Symbol	Min	Typ	Max	Unit
-----------------	--------	-----	-----	-----	------

ON CHARACTERISTICS

DC Current Gain ($I_C=-1\text{ mAdc}, V_{CE}=-6.0\text{ Vdc}$)	h_{FE}	120	-	560	-
Collector-Emitter Saturation Voltage ($I_C=-50\text{ mAdc}, I_B=-5\text{ mAdc}$)	$V_{CE(sat)}$	-	-	-0.5	Vdc
Output Capacitance ($V_{CB}=-12\text{ Vdc}, I_E=0\text{ A}, f=1\text{ MHz}$)	C_{ob}	-	4.0	5.0	PF
Current-Gain-Bandwidth Product ($I_E=2\text{ mAdc}, V_{CE}=-12\text{ Vdc}, f=30\text{ MHz}$)	f_T	-	140	-	MHz

CLASSIFICATION OF h_{FE}

Item	Q	R	S
Range	120-270	180-390	270-560
Marking	FQ	FR	FS






FIG.7 Collector-emitter saturation voltage vs. collector current (I)




FIG.8 Gain bandwidth product vs. emitter current




FIG.9 Collector output capacitance vs. collector-base voltage
Emitter input capacitance vs. emitter-base voltage

SC-89 Outline Demensions

Unit:mm

