

RoHS Compliant Product

A suffix of "-C" specifies halogen & lead-free



## FEATURES

- Optimum for RF Amplification of FM/AM Radios
- High Transition Frequency  $f_T$

## CLASSIFICATION OF $h_{FE}$

Product-Rank	2SC1359-B	2SC1359-C
Range	70~140	110~220

## TO-92



## ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	$V_{CBO}$	30	V
Collector to Emitter Voltage	$V_{CEO}$	20	V
Emitter to Base Voltage	$V_{EBO}$	5	V
Collector Current - Continuous	$I_C$	30	mA
Collector Power Dissipation	$P_C$	400	mW
Thermal Resistance From Junction To Ambient	$R_{\theta JA}$	312	$^\circ\text{C} / \text{W}$
Junction, Storage Temperature	$T_J, T_{STG}$	150, -55~150	$^\circ\text{C}$

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	30	-	-	V	$I_C=0.1\text{mA}, I_E=0$
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	20	-	-	V	$I_C=1\text{mA}, I_B=0$
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	5	-	-	V	$I_E=0.1\text{mA}, I_C=0$
Collector Cut - Off Current	$I_{CBO}$	-	-	0.1	$\mu\text{A}$	$V_{CB}=10\text{V}, I_E=0$
Emitter Cut - Off Current	$I_{EBO}$	-	-	0.1	$\mu\text{A}$	$V_{EB}=5\text{V}, I_C=0$
DC Current Gain	$h_{FE}$	70	-	220		$V_{CE}=10\text{V}, I_C=1\text{mA}$
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	-	-	0.2	V	$I_C=15\text{mA}, I_B=1.5\text{mA}$
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	-	-	1.2	V	$I_C=15\text{mA}, I_B=1.5\text{mA}$
Transition Frequency	$f_T$	150	-	-	MHz	$V_{CE}=10\text{V}, I_C=1\text{mA}, f=200\text{MHz}$