

2SC1623

Silicon PNP Epitaxial Type Transistor

Features

- High DC current gain: $h_{FE}=200$ TYP

($V_{CE}=6.0V, I_C=1.0mA$).

- High Voltage: $V_{CEO}=50V$
- RoHS compliant package

Applications

NPN Silicon Epitaxial Planar Transistor.

Audio frequency general purpose amplifier.





Packing & Order Information

3,000/Reel



**RoHS
COMPLIANT**

Graphic symbol



Symbol	MILLIMETERS	
	MIN	MAX
A	0.8	1.2
A1	0	0.1
A2	0.7	1.1
b	0.3	0.5
c	0.1	0.2
D	2.7	3.1
E	2.6	3
E1	1.4	1.8
e	0.95 BSC	
e1	1.9 BSC	
L	0.3	0.6
θ1	7° NOM	

2SC1623

Silicon PNP Epitaxial Type Transistor

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Parameter	Value	Unit
V _{CBO}	Collector-Base Voltage	60	V
V _{CEO}	Collector-Emitter Voltage	50	V
V _{EBO}	Emitter-Base Voltage	5	V
I _C	Collector Current	100	mA
P _C	Collector Dissipation	200	mW
T _j , T _{stg}	Junction and Storage Temperature	-55 to +150	°C

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Symbol	Parameter	Test Conditions	MIN	TYP	MAX	UNIT
V _{(BR)CBO}	Collector-base breakdown voltage	I _C = 100μA , I _E = 0	60			V
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C = 1mA , I _B = 0	50			V
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E = 100μA , I _C = 0	5			V
I _{CBO}	Collector cut-off current	V _{CB} = 60 V , I _E = 0				μA
I _{EBO}	Emitter cut-off current	V _{EB} = 5 V , I _C = 0				μA
h _{FE}	DC current gain	V _{CE} = 6 V , I _C = 1 mA	90	200	600	
V _{CE(sat)}	Collector-emitter saturation voltage	I _C = 100mA , I _B = 10mA		0.15	0.3	V
V _{BE(sat)}	Base-emitter saturation voltage	I _C = 100mA , I _B = 10mA		0.86	1.0	V
V _{BE}	Base Emitter Voltage	V _{CE} = 6 V , I _C = 1 mA	0.55	0.62	0.65	V
f _T	Transition frequency	V _{CE} = 6 V , I _E = -10 mA		250		MHz
C _{ob}	Output capacitance	V _{CB} = 6 V , I _E = 0 f = 1.0MHz		3.0		pF


CLASSIFICATION OF h_{FE}(1)

Rank	L4	L5	L6	L7
Range	90-180	135-270	200-400	300-600
Marking	L4	L5	L6	L7

2SC1623

Silicon PNP Epitaxial Type Transistor

■ RATINGS AND CHARACTERISTIC CURVES



2SC1623

Silicon PNP Epitaxial Type Transistor

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Bruckewell Technology Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Bruckewell"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Bruckewell makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Bruckewell disclaims

- (i) Any and all liability arising out of the application or use of any product.
- (ii) Any and all liability, including without limitation special, consequential or incidental damages.
- (iii) Any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Bruckewell's knowledge of typical requirements that are often placed on Bruckewell products in generic applications.

Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time.

Product specifications do not expand or otherwise modify Bruckewell's terms and conditions of purchase, including but not limited to the warranty expressed therein.