

**TRIPLE DIFFUSED PLANER TYPE  
HIGH SPEED SWITCHING**


**■ Features**

- High speed switching
- High D.C. current gain
- Low saturation voltage
- High reliability

**■ Applications**

- Switching regulators
- DC-DC converter
- Solid state relay
- General purpose power amplifiers

**■ Outline Drawings**



**■ Maximum ratings and characteristics**

**● Absolute maximum ratings (Tc=25°C unless otherwise specified)**

Item	Symbol	Ratings	Unit
Collector-Base voltage	V <sub>CBO</sub>	80	V
Collector-Emitter voltage	V <sub>CEO</sub>	50	V
Emitter-Base voltage	V <sub>EBO</sub>	10	V
Collector current	I <sub>C</sub>	4	A
	-I <sub>C</sub>	1	A
Base current	I <sub>B</sub>	1	A
Collector power dissipation	P <sub>C</sub>	25	W
Operating junction temperature	T <sub>j</sub>	+150	°C
Storage temperature	T <sub>stg</sub>	-55 to +150	°C


**● Electrical characteristics (Tc =25°C unless otherwise specified)**

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector-Base voltage	V <sub>CBO</sub>	I <sub>CBO</sub> = 0.1mA	80			V
Collector-Emitter voltage	V <sub>CEO</sub>	I <sub>CEO</sub> = 10mA	50			V
Collector-Emitter voltage	V <sub>CEO(SUS)</sub>	I <sub>C</sub> = 1A	50			V
Emitter-Base voltage	V <sub>EBO</sub>	I <sub>EBO</sub> = 0.1mA	10			V
Collector-Base leakage current	I <sub>CBO</sub>	V <sub>CBO</sub> = 80V			0.1	mA
Emitter-Base leakage current	I <sub>EBO</sub>	V <sub>EBO</sub> = 10V			0.1	mA
D.C. current gain	h <sub>FE</sub>	I <sub>C</sub> = 0.5A, V <sub>CE</sub> = 5V	250			
Collector-Emitter saturation voltage	V <sub>CE(Sat)</sub>	I <sub>C</sub> = 1A, I <sub>B</sub> = 50mA			0.5	V
Base-Emitter saturation voltage	V <sub>BE(Sat)</sub>				1.5	V
*1	ton	I <sub>C</sub> = 2A, I <sub>B1</sub> = 200mA			0.5	μs
Switching time	t <sub>stg</sub>	I <sub>B2</sub> = -200mA, R <sub>L</sub> = 5 ohm			3.0	μs
	t <sub>f</sub>	P <sub>w</sub> = 20μs, Duty < 2%			0.8	μs


**● Thermal characteristics**

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal resistance	R <sub>th(j-c)</sub>	Junction to case			5.0	°C/W


## ■ Characteristics




Collector Output Characteristics



DC Current Gain



Base and Collector Saturation Voltage



Safe Operating Area

## \*1 Switching Time Test Circuit

