

Power Transistor (80V, 1A)


2SD1898 / 2SD1733 / 2SD1768S / 2SD1863

Features

- 1) High VCEO, VCEO=80V
- 2) High Ic, Ic=1A (DC)
- 3) Good hFE linearity
- 4) Low Vce (sat)
- 5) Complements the 2SB1260 / 2SB1241 / 2SB1181

●Structure

Epitaxial planer type NPN silicon transistor



● Absolute maximum ratings (Ta=25°C)

Parameter		Symbol	Limits	Unit
Collector-base voltage		Vсво	120	V
Collector-emitter voltage		Vceo	80	V
Emitter-base voltage		Vево	5	V
Collector current		I.	1	A (DC)
		lc lc	2	A (Pulse) *1
Collector power dissipation	2SD1898		0.5	W
			2	W *3
	2SD1733	D.	1	W
		Pc	10	W (Tc=25°C)
	2SD1768S		0.3	W
	2SD1863		1	W *2
Junction temperature		Tj	150	°C
Storage temperature		Tstg	-55 to +150	°C

●Electrical characteristics (Ta=25°C)

Parameter		Symbol	Min.	Тур.	Max.	Unit	Conditions	
Collector-base breakdown voltage		ВУсво	120	_	_	V	Ic=50μA	
Collector-emitter breakdown voltage		BV _{CEO}	80	_	_	V	Ic=1mA	
Emitter-base breakdown voltage		BV _{EBO}	5	_	_	V	Iε=50μA	
Collector cutoff current		Ісво	_	_	1	μΑ	Vcb=100V	
Emitter cutoff current		ІЕВО	-	_	1	μΑ	V _{EB} =4V	
DC current transfer ratio	2SD1863	* hfe	120	_	390	_	Vce=3V, Ic=0.5A	
	2SD1733, 2SD1898		120	_	390	_		
	2SD1768S		120	_	390	_		
Collector-emitter saturation voltage		VCE(sat)	_	0.15	0.4	V	Ic/I _B =500mA/20mA	
Transition frequency		f⊤	_	100	_	MHz	Vc==10V, I==-50mA, f=100MHz	
Output capacitance		Cob	ı	20	_	pF	Vcb=10V, Ie=0A, f=1MHz	

^{*} Measured using pulse current

●Packaging specifications and hfe

		Package	Taping			
		Code	T100	TL	TP	TV2
Туре	hfe	Basic ordering unit (pieces)	1000	2500	5000	2500
2SD1898	QR		0	-	_	-
2SD1733	QR		_	0	_	_
2SD1768S	QR		_	-	0	-
2SD1863	QR		_	_	_	0

hFE values are classified as follows:

Item	Q	R
hfe	120 to 270	180 to 390

^{*1} Pw=20ms, duty=1 / 2
*2 Printed circuit board 1.7mm thick, collector copper plating 1cm² or larger.
*3 When mounted on a 40×40×0.7mm ceramic board.

•Electrical characteristic curves




Fig.1 Grounded emitter propagation characteristics




Fig.4 Collector-emitter saturation voltage vs. collector current




Fig.7 Safe operating area (2SD1863)




Fig.2 Grounded emitter output characteristics




Fig.5 Gain bandwidth product vs. emitter current




Fig.8 Safe operating area (2SD1898)




Fig.3 DC current gain vs. collector current




Fig.6 Collector output capacitance vs. collector-base voltage Emitter input capacitance vs. emitter-base voltage

Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/