

**Micro Commercial Components** 



**Micro Commercial Components** 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 (818) 701-4939 Fax:


## 2SD2012

### Features

- High DC Current Gain:  $h_{FE(1)}=100$  (Min.)
- .
- Low Saturation Voltage:  $V_{CE(sat)}=1.0V$  (Max.) High Power Dissipation:  $P_{C}=25W$  ( $T_{C}=25^{\circ}C$ ) Lead Free Finish/RoHS Compliant (Note1) ("P" Suffix designates RoHS Compliant. See ordering information) .
- Epoxy meets UL 94 V-0 flammability rating .
- Moisure Sensitivity Level 1 Maximum Ratinds

IVIdXIIII		-						
Symbol	Rating	R	Rating		Unit			
V <sub>CEO</sub>	Collector-Emitter Voltage	60			V			
V <sub>CBO</sub>	Collector-Base Voltage	60			V			
V <sub>EBO</sub>	Emitter-Base Voltage	7.0			V			
c	Collector Current		3.0		А			
В	Base Current		0.5		A			
P <sub>C</sub>	Collector power dissipation $T_A=25^{\circ}C$ $T_C=25^{\circ}C$		2.0 25		W			
TJ	Junction Temperature	-55 to +150			°C			
T <sub>STG</sub>	Storage Temperature	-55 to +150			°C			
Electrical Characteristics @ 25°C Unless Otherwise Specified								
Symbol	Parameter	Min	Тур	Max	Units			
OFF CHARACTERISTICS								
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage (b=50mAdc, b=0)	60			Vdc			
I <sub>сво</sub>	Collector-Base Cutoff Current (V <sub>CB</sub> =60Vdc, =0)			100	uAdc			
I <sub>EBO</sub>	Emitter-Base Cutoff Current (V <sub>EB</sub> =7.0Vdc, <u>k</u> =0)			100	uAdc			
ON CHARACTERISTICS								
h <sub>FE(1)</sub>	Forward Current Transfer ratio (t=0.5Adc, V <sub>CE</sub> =5.0Vdc)	100		320				
h <sub>FE(1)</sub> h <sub>FE(2)</sub>		100 20		320				
.,	(L=0.5Adc, V <sub>CE</sub> =5.0Vdc) Forward Current Transfer ratio		  0.4		  Vdc			
h <sub>FE(2)</sub>	( $\[l]$ =0.5Adc, V <sub>CE</sub> =5.0Vdc) Forward Current Transfer ratio ( $\[l]$ =2.0Adc, V <sub>CE</sub> =5.0Vdc) Collector-Emitter Saturation Voltage	20	 0.4 0.75					

# **NPN Silicon Power Transistors**



DIMENSIONS							
	INCHES		MM				
DIM	MIN	MAX	MIN	MAX	NOTE		
A	.560	.625	14.22	15.88			
В	.380	.420	9.65	10.67			
С	.140	.190	3.56	4.82			
D	.020	.045	0.51	1.14			
F	.139	.161	3.53	4.09	Ø		
G	.190	.110	2.29	2.79			
Н		.250		6.35			
J	.012	.025	0.30	0.64			
К	.500	.580	12.70	14.73			
L	.045	.060	1.14	1.52			
Ν	.190	.210	4.83	5.33			
Q	.100	.135	2.54	3.43			
R	.080	.115	2.04	2.92			
S	.045	.055	1.14	1.39			
Т	.230	.270	5.84	6.86			
U		.050		1.27			
V	.045		1.15				

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

(V<sub>CE</sub>=5.0Vdc, Ŀ=0.5Adc)

**Collector Output Capacitance** 

(V<sub>CB</sub>=10Vdc, **k**=0, f=1.0MHz)

www.mccsemi.com


35

C<sub>ob</sub>

pF

## 2SD2012







www.mccsemi.com

### 2SD2012









# www.mccsemi.com



### **Ordering Information :**

Device	Packing
Part Number-BP	Bulk; 1Kpcs/Box

### **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## www.mccsemi.com