



## SMD Connectors

### SMDblank/ 1

Terminal Block, 1 pole, Current Rating: 4 A, Voltage Rating: 320 V,  
Connection Type: screwless



### Order Info

<b>Reference Number (ref. no.)</b>	351901
<b>Applications</b>	Lighting
<b>PU</b>	2,800 (tape-on-reel)
<b>EAN</b>	4028012123865

### Type

<b>Type</b>	Terminal Block
<b>Number of poles</b>	1 pole
<b>Clamping Units per Pole</b>	1
<b>Connection Type</b>	screwless

### Technical Data

<b>Voltage Rating</b>	320 V
<b>Current Rating</b>	4 A
<b>Contact Material</b>	Spring Steel, Copper
<b>Core Cross-Section min.</b>	horizontal: 0.2 mm <sup>2</sup> . vertikal: 0.5 mm <sup>2</sup> mm <sup>2</sup>
<b>Horizontal Core Cross-Section min.</b>	0.2 mm <sup>2</sup>
<b>Vertical Core Cross-Section min.</b>	0.5 mm <sup>2</sup>
<b>Core Cross-Section max.</b>	0.5 mm <sup>2</sup>
<b>max. Ambient Temperature Operation</b>	85 °C
<b>Type of Conductor Solid</b>	yes
<b>Type of Conductor Flexible</b>	yes
<b>Type of Conductor Stranded</b>	yes
<b>Stripping Length</b>	horizontal mm
<b>Lower Limit Temperature</b>	-40 °C
<b>Upper Limit Temperature</b>	105 °C
<b>Vertical Stripping Length</b>	8.0-9.0 mm
<b>Horizontal Stripping Length</b>	3.0 mm

### Accessories

<b>SMDblank WKZ</b>	351999
---------------------	--------