


40HF(R) SERIES

STANDARD RECOVERY DIODES

Stud Version

Features

- High surge current capability
- Stud cathode and stud anode version
- Leaded version available
- Types up to 1600V V_{RRM}




Typical Applications

- Battery charges
- Converters
- Power supplies
- Machine tool controls
- Welding

Major Ratings and Characteristics

| Parameters | 40HF(R) | | Units |
|------------------|-------------|-------------|------------------|
| | 10 to 120 | 140, 160 | |
| $I_{F(AV)}$ | 40 | 40 | A |
| @ T_c | 140 | 110 | °C |
| $I_{F(RMS)}$ | 62 | | A |
| I_{FSM} @ 50Hz | 570 | | A |
| @ 60Hz | 595 | | A |
| I^2t @ 50Hz | 1600 | | A ² s |
| @ 60Hz | 1450 | | A ² s |
| V_{RRM} range | 100 to 1200 | 1400, 1600 | V |
| T_j range | - 65 to 190 | - 65 to 160 | °C |



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

40HF(R) Series

ELECTRICAL SPECIFICATIONS

Voltage Ratings

| Type number | Voltage Code | V_{RRM} , maximum repetitive peak reverse voltage V | V_{RSM} , maximum non-repetitive peak reverse voltage V | I_{RRM} max. @ $T_J = T_J$ max. mA |
|-------------|--------------|--|--|--|
| 40HF(R) | 10 | 100 | 200 | 9 |
| | 20 | 200 | 300 | |
| | 40 | 400 | 500 | |
| | 60 | 600 | 700 | |
| | 80 | 800 | 900 | |
| | 100 | 1000 | 1100 | |
| | 120 | 1200 | 1300 | |
| | 140 | 1400 | 1500 | 4.5 |
| | 160 | 1600 | 1700 | |

Forward Conduction

| Parameter | 40HF(R) | | Units | Conditions | |
|--|-----------|----------|--------------------|--|-----------------------|
| | 10 to 120 | 140, 160 | | | |
| $I_{F(AV)}$ Max. average forward current @ Case temperature | 40 | 40 | A | 180° conduction, half sine wave | |
| $I_{F(RMS)}$ Max. RMS forward current | 140 | 110 | °C | | |
| I_{FSM} Max. peak, one-cycle forward, non-repetitive surge current | 62 | | A | | |
| I_{FSM} Max. peak, one-cycle forward, non-repetitive surge current | 570 | | | t = 10ms | No voltage reappplied |
| | 595 | | | t = 8.3ms | reappplied |
| | 480 | | | t = 10ms | 100% V_{RRM} |
| | 500 | | | t = 8.3ms | reappplied |
| I^2t Maximum I^2t for fusing | 1600 | | A ² s | t = 10ms | No voltage reappplied |
| | 1450 | | | t = 8.3ms | reappplied |
| | 1150 | | | t = 10ms | 100% V_{RRM} |
| | 1050 | | | t = 8.3ms | reappplied |
| I^2vt Maximum I^2vt for fusing | 16000 | | A ² v s | t = 0.1 to 10ms, no voltage reappplied | |
| $V_{F(TO)}$ Value of threshold voltage (up to 1200V) | 0.65 | | V | $T_J = T_J$ max. | |
| $V_{F(TO)}$ Value of threshold voltage (for 1400V, 1600V) | 0.76 | | | $T_J = T_J$ max. | |
| r_f Value of forward slope resistance (up to 1200V) | 4.29 | | mΩ | $T_J = T_J$ max. | |
| r_f Value of forward slope resistance (for 1400V, 1600V) | 3.8 | | | $T_J = T_J$ max. | |
| V_{FM} Max. forward voltage drop | 1.30 | 1.50 | V | $I_{pk} = 125A$, $T_J = 25^\circ C$, $t_p = 400\mu s$ rectangular wave | |

40HF(R) Series

Thermal and Mechanical Specifications

| Parameter | 40HF(R) | | Units | Conditions |
|--|----------------|------------|--------|--|
| | 10 to 120 | 140 to 160 | | |
| T_J Max. junction operating temperature range | -65 to 190 | -65 to 160 | °C | |
| T_{stg} Max. storage temperature range | -65 to 190 | -65 to 160 | | |
| R_{thJC} Max. thermal resistance, junction to case | 0.95 | | K/W | DC operation |
| R_{thCS} Max. thermal resistance, case to heatsink | 0.25 | | | Mounting surface, smooth, flat and greased |
| T Max. allowed mounting torque $\pm 10\%$ | 2.3 - 3.4 | | Nm | Not lubricated threads |
| | 20 - 30 | | lbf·in | |
| wt Approximate weight | 17 (0.6) | | g (oz) | unleaded device |
| Case style | DO-203AB (DO5) | | | See Outline Table |

ΔR_{thJC} Conduction

(The following table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC)

| Conduction angle | Sinusoidal conduction | Rectangular conduction | Units | Conditions |
|------------------|-----------------------|------------------------|-------|-----------------|
| 180° | 0.14 | 0.10 | K/W | $T_J = T_{max}$ |
| 120° | 0.16 | 0.17 | | |
| 90° | 0.21 | 0.22 | | |
| 60° | 0.30 | 0.31 | | |
| 30° | 0.50 | 0.50 | | |

Ordering Information Table

| Device Code | |
|-------------|--|
| | <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; padding: 2px 5px;">40</div> <div style="border: 1px solid black; padding: 2px 5px;">HF</div> <div style="border: 1px solid black; padding: 2px 5px;">R</div> <div style="border: 1px solid black; padding: 2px 5px;">160</div> <div style="border: 1px solid black; padding: 2px 5px;">M</div> </div> <div style="display: flex; justify-content: space-around; margin-top: 5px;"> ① ② ③ ④ ⑤ </div> |
| 1 | - 40 = Standard device 41 = Not isolated lead 42 = Isolated lead with silicone sleeve (Red = Reverse polarity) (Blue = Normal polarity) |
| 2 | - Standard diode |
| 3 | - None = Stud Normal Polarity (Cathode to Stud) R = Stud Reverse Polarity (Anode to Stud) |
| 4 | - Voltage code: Code x 10 = V_{RRM} (See Voltage Ratings table) |
| 5 | - None = Stud base DO-203AB (DO-5) 1/4" 28UNF-2A M = Stud base DO-203AB (DO-5) M6 X 1 |

40HF(R) Series

Outlines Table

