


500 mW DO-35 Hermetically Sealed Glass Zener Voltage Regulators



Maximum Ratings (Note 1)

Rating	Symbol	Value	Units
Maximum Steady State Power Dissipation @TL≤75°C, Lead Length = 3/8"	P _D	500	mW
Derate Above 75°C		4.0	mW/°C
Operating and Storage Temperature Range	T _J , T _{stg}	-65 to +200	°C

Note 1: Some part number series have lower JEDEC registered ratings.



L = Logo
79Cxxx = BZX79CxxxDevice Code

Specification Features:

- Zener Voltage Range = 2.4V to 200V
- ESD Rating of Class 3 (>6 KV) per Human Body Model
- DO-35 Package (DO-204AH)
- Double Slug Type Construction
- Metallurgical Bonded Construction
- RoHS Compliant
- Solder Hot Dip Tin (Sn) Lead Finish


Specification Features:

Case : Double slug type, hermetically sealed glass

Finish : All external surfaces are corrosion resistant and leads are readily solderable

Polarity : Cathode indicated by polarity band

Mounting: Any



ELECTRICAL CHARACTERIZATION ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Device (Note 2.)	Device Marking	Zener Voltage (Note 3.)			Zener Impedance (Note 4.)	Leakage Current		$\theta_{V_{BR}}$		C $V_Z = 0$, $F = 1.0\text{MHz}$
		V_Z (Volts)		@ I_{ZT}	Z_{ZT} @ I_{ZT}	I_R @ V_R		(mV/°C)		
		Min	Max	(mA)	(Ω)	($\mu\text{A Max}$)	(Volts)	Min	Max	
BZX79C2V4	79C2V4	2.2	2.6	5	100	100	1	-3.5	0	255
BZX79C2V7	79C2V7	2.5	2.9	5	100	75	1	-3.5	0	230
BZX79C3V0	79C3V0	2.8	3.2	5	95	50	1	-3.5	0	215
BZX79C3V3	79C3V3	3.1	3.5	5	95	25	1	-3.5	0	200
BZX79C3V6	79C3V6	3.4	3.8	5	90	15	1	-3.5	0	185
BZX79C3V9	79C3V9	3.7	4.1	5	90	10	1	-3.5	0.3	175
BZX79C4V3	79C4V3	4.0	4.6	5	90	5	1	-3.5	1.0	160
BZX79C4V7	79C4V7	4.4	5.0	5	80	3	2	-3.5	0.2	130
BZX79C5V1	79C5V1	4.8	5.4	5	60	2	2	-2.7	1.2	110
BZX79C5V6	79C5V6	5.2	6.0	5	40	1	2	-2.0	2.5	95
BZX79C6V2	79C6V2	5.8	6.6	5	10	3	4	0.4	3.7	90
BZX79C6V8	79C6V8	6.4	7.2	5	15	2	4	1.2	4.5	85
BZX79C7V5	79C7V5	7.0	7.9	5	15	1	5	2.5	5.3	80
BZX79C8V2	79C8V2	7.7	8.7	5	15	0.7	5	3.2	6.2	75
BZX79C9V1	79C9V1	8.5	9.6	5	15	0.5	6	3.8	7.0	70
BZX79C10	79C10	9.4	10.6	5	20	0.2	7	4.5	8	70
BZX79C11	79C11	10.4	11.6	5	20	0.1	8	5.4	9	65
BZX79C12	79C12	11.4	12.7	5	25	0.1	8	6	10	65
BZX79C13	79C13	12.4	14.1	5	30	0.1	8	7	11	60
BZX79C15	79C15	13.8	15.6	5	30	0.05	10.5	9.2	13	55
BZX79C16	79C16	15.3	17.1	5	40	0.05	11.2	10.4	14	52
BZX79C18	79C18	16.8	19.1	5	45	0.05	12.6	12.9	16	47
BZX79C20	79C20	18.8	21.2	5	55	0.05	14	14.4	18	36
BZX79C22	79C22	20.8	23.3	5	55	0.05	15.4	16.4	20	34
BZX79C24	79C24	22.8	25.6	5	70	0.05	16.8	18.4	22	33
BZX79C27	79C27	25.1	28.9	2	80	0.05	18.9		23.5	30
BZX79C30	79C30	28	32	2	80	0.05	21		26	27
BZX79C33	79C33	31	35	2	80	0.05	23.1		29	25
BZX79C36	79C36	34	38	2	90	0.05	25.2		31	23
BZX79C39	79C39	37	41	2	130	0.05	27.3		34	21
BZX79C43	79C43	40	46	2	150	0.05	30.1		37	21
BZX79C47	79C47	44	50	2	170	0.05	32.9		40	19
BZX79C51	79C51	48	54	2	180	0.05	35.7		44	19
BZX79C56	79C56	52	60	2	200	0.05	39.2		47	18
BZX79C62	79C62	58	66	2	215	0.05	43.4		51	17
BZX79C68	79C68	64	72	2	240	0.05	47.6		56	17
BZX79C75	79C75	70	79	2	255	0.05	52.5		60	16.5
BZX79C82	79C82	77	87	2	280	0.1	62	46	95	29
BZX79C91	79C91	85	96	2	300	0.1	69	51	107	28
BZX79C100	79C100	94	106	1	500	0.1	76	57	119	27

 VF Forward Voltage = 1.5V max @ $I_F = 100\text{mA}$ for all types

ELECTRICAL CHARACTERIZATION ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Device (Note 2.)	Device Marking	Zener Voltage (Note 3.)		Zener Impedance (Note 4.)	Leakage Current		$\theta_{V_{BR}}$		C $V_Z = 0$, $F = 1.0\text{MHz}$	
		V_Z (Volts)		@ I_{ZT}	Z_{ZT} @ I_{ZT}	I_R @ V_R		(mV/°C)		
		Min	Max	(mA)	(Ω)	($\mu\text{A Max}$)	(Volts)	Min		Max
BZX79C110	79C110	104	116	1	650	0.1	84	63	131	26
BZX79C120	79C120	114	127	1	800	0.1	91	69	144	24
BZX79C130	79C130	124	141	1	950	0.1	99	75	158	23
BZX79C150	79C150	138	156	1	1250	0.1	114	87	185	21
BZX79C160	79C160	153	171	1	1400	0.1	122	93	200	20
BZX79C180	79C180	168	191	1	1700	0.1	137	105	228	18
BZX79C200	79C200	188	212	1	2000	0.1	152	120	255	17

V_F Forward Voltage = 1.5V max @ $I_F = 100\text{mA}$ for all types

2. TOLERANCE AND VOLTAGE DESIGNATION

The type numbers listed have zener voltage min/max limits as shown.

3. REVERSE ZENER VOLTAGE (V_Z)


Reverse zener voltage is measured under pulse conditions such that T_J is no more than 2°C above T_A .

4. ZENER IMPEDANCE (Z_Z) DERIVATION

Z_{ZT} is measured by dividing the AC voltage drop across the device by the AC current applied. The specified limits are for $I_{Z(AC)} = 0.1 I_{Z(DC)}$ with AC frequency = 60Hz.

Package Outline

Case Outline




DIM	DO-35			
	Millimeters		Inches	
	Min	Max	Min	Max
A	0.46	0.56	0.018	0.022
B	3.05	5.08	0.120	0.200
C	25.40	38.10	1.000	1.500
D	1.52	2.29	0.060	0.090

Note: all dimensions are within JEDEC standard.

This datasheet presents technical data of Tak Cheong's Zener Diodes. Complete specifications for the individual devices are provided in the form of datasheets. A comprehensive Selector Guide is included to simplify the task of choosing the best set of components required for a specific application. For additional information, please visit our website <http://www.takcheong.com>.

Although information in this datasheet has been carefully checked, no responsibility for the inaccuracies can be assumed by Tak Cheong. Please consult your nearest Tak Cheong's sales office for further assistance.

Tak Cheong reserves the right to make changes without further notice to any products herein to further improve reliability, function or design, cost and productivity.

TAK CHEONG® and  are registered trademarks of Tak Cheong Electronics (Holdings) Co., Ltd.