


Signal conditioner SCDN-2V-EC4-PNLK-L1

Part number: 803555

FESTO



Data sheet

Feature	Value
Type code	SCDN
Electrical connection for input 1, connection pattern	00995428
Electrical connection 1, connection type	Plug
Electrical connection 2, connection technology	Connection diagram EC
Electrical connection 2, connection type	2x socket
KC characters	KC EMC
Electrical connection 1, connection technology	Connection diagram L1J
Electrical connection 2, connection pattern	00995750
Electrical connection 1, number of pins/wires	4
Electrical connection 2, number of pins/wires	4
Symbol	00995687
Certification	RCM compliance mark c UL us - Listed (OL)
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
Certificate issuing authority	UL E322346
Note on materials	RoHS-compliant
Measured variable	Voltage
Signal range	0 - 10 V
Ambient temperature	0 °C ... 50 °C
Typical sampling interval	1 ms
Accuracy in ± % FS	0.5 %FS
Repetition accuracy in ± %FS	0.2 %FS
Switching output	2 x PNP or 2 x NPN switchable
Switching function	Freely programmable
Switching element function	N/C contact/N/O contact switchable
Max. output current	100 mA
Short-circuit protection	yes
Protocol	IO-Link®
IO-Link®, protocol version	Device V 1.1
IO-Link®, profile	Smart sensor profile
IO-Link®, function classes	Binary data channel (BDC) Process data variable (PDV) Identification Diagnostics Teach channel

Feature	Value
IO-Link®, communication mode	COM2 (38,4 kBd)
IO-Link®, SIO mode support	Yes
IO-Link®, port class	A
IO-Link®, process data width OUT	0 Byte
IO-Link®, process data width IN	5 Byte
IO-Link®, process data content IN	14 bit PDV (InA measured value) 14 bit PDV (InB measured value) 2 bit BDC (measured value monitoring)
IO-Link®, minimum cycle time	5 ms
IO-Link®, data memory required	500 byte
DC operating voltage range	15 V ... 30 V
Reverse polarity protection	for all electrical connections
Type of mounting	Front panel mounting With wall/surface bracket
Product weight	23 g
Housing material	PA-reinforced
Display type	Illuminated LCD, multi-color
Setting options	IO-Link® Teach-in Via display and pushbuttons
Protection against tampering	IO-Link® PIN code
Degree of protection	IP40
Corrosion resistance class (CRC)	2 - Moderate corrosion stress