

ABF22 THRU ABF210


SINGLE PHASE 2.0AMP SURFACE MOUNT GLASS PASSIVATED BRIDGE RECTIFIER

Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Designed for surface mount application
- Plastic material-UL flammability 94V-0

Mechanical Data

- Case: SOPA-4, molded plastic
- Terminals: plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting position: Any
- Marking: type number



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single Phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	ABF22	ABF24	ABF26	ABF28	ABF210	UNITS	
Peak Repetitive Reverse Voltage	V_{RRM}							
Working Peak Reverse Voltage	V_{RWM}	200	400	600	800	1000	V	
DC Blocking Voltage	V_{DC}							
RMS Reverse Voltage	V_{RMS}	140	280	420	560	700	V	
Average Rectified Output Current @ $T_A = 50^\circ C$	I_o	2.0						A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	60						A
Forward Voltage per element @ $I_F = 2.0A$	V_{FM}	1.1						V
Peak Reverse Current @ $T_A = 25^\circ C$ At Rated DC Blocking Voltage @ $T_A = 125^\circ C$	I_R	5.0 500						μA
Typical Thermal Resistance per leg	$R_{\theta JA}$	62.5						°C/W
	$R_{\theta JL}$	25						
Operating and Storage Temperature Range	T_J, T_{STG}	-55to+150						°C

FIG.1 FORWARD CURRENT DERATING CURVE




FIG.2 TYPICAL FORWARD CHARACTERISTICS




FIG.3 MAXIMUM NON-REPETITIVE SURGE CURRENT




Fig. 4 T typical Reverse Characteristics (per element)

