



- Cw/w: 50PF Typ @ 100KHz, 0.2V
- Polarity: 1-20, 4-17, 6-15, 9-12 In-Phase
- LL: 0.5μH Max @ 100KHz, 0.2V
- DCR: 0.9Ω Max
- Operating Temp: 0°C to 70°C

**Electrical Specifications @ 25°C**


Part Number	OCL(uH Min) @ 100kHz, 200mV With 8mA DC Bias	Turns Ratio chip: cable (±5%)	Insertion Loss (dB Max)	Return Loss (dB Min)			
	0.3-100MHz			0.3-30MHz	40MHz	50MHz	60-80MHz
AHTD-2003S	350	1CT:1CT(TX)/1CT:1CT(RX)	-1.1	-18	-16	-14.5	-12

**Electrical Specifications @ 25°C**

Part Number	Common Mode Rejection (dB Min)			Cross Talk (dB Min)		Isolation HI-POT (Vrms) 60S
	0.3-30MHz	60MHz	80-100MHz	0.3-30MHz	60-100MHz	
AHTD-2003S	-40	-35	-30	-42	-35	1500

All specifications subject to change without notice.

**MECHANICAL**



Dimensions: inch(mm)  
Unless otherwise specified, all tolerances are ±0.010(0.25)

**SCHEMATICS**

