



N-Channel MOSFET

AO4444 (KO4444)

■ Features

- $V_{DS} = 30V$
- $I_D = 20 A$ ($V_{GS} = 10V$)
- $R_{DS(ON)} < 5.5m\Omega$ ($V_{GS} = 10V$)
- $R_{DS(ON)} < 7.5m\Omega$ ($V_{GS} = 4.5V$)

■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current	I_D	$T_A=25^\circ C$	20
		$T_A=70^\circ C$	17
Pulsed Drain Current	I_{DM}	80	A
Power Dissipation	P_D	$T_A=25^\circ C$	3
		$T_A=70^\circ C$	2.1
Thermal Resistance.Junction- to-Ambient	R_{thJA}	$t \leq 10s$	40
		Steady-State	75
Thermal Resistance.Junction- to-Lead	R_{thJL}	24	$^\circ C/W$
Junction Temperature	T_J	150	$^\circ C$
Storage Temperature Range	T_{stg}	-55 to 150	

N-Channel MOSFET

AO4444 (KO4444)

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Drain-Source Breakdown Voltage	V _{DSS}	I _D =250μA, V _{GS} =0V	30			V	
Zero Gate Voltage Drain Current	I _{DSS}	V _{Ds} =24V, V _{GS} =0V			1	μA	
		V _{Ds} =24V, V _{GS} =0V, T _J =55°C			5		
Gate-Body Leakage Current	I _{less}	V _{Ds} =0V, V _{GS} =±20V			±100	nA	
Gate Threshold Voltage	V _{GS(th)}	V _{Ds} =V _{GS} , I _D =250 μA	1		3	V	
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =10V, I _D =20A			5.5	mΩ	
		V _{GS} =10V, I _D =20A T _J =125°C			6.2		
		V _{GS} =4.5V, I _D =15A			7.5		
On State Drain Current	I _{D(ON)}	V _{GS} =10V, V _{Ds} =5V	60			A	
Forward Transconductance	g _{FS}	V _{Ds} =5V, I _D =20A		106		S	
Input Capacitance	C _{iss}	V _{GS} =0V, V _{Ds} =15V, f=1MHz		3200	3840	pF	
Output Capacitance	C _{oss}			590			
Reverse Transfer Capacitance	C _{rss}			414			
Gate Resistance	R _g	V _{GS} =0V, V _{Ds} =0V, f=1MHz		0.54	0.7	Ω	
Total Gate Charge (10V)	Q _g	V _{GS} =4.5V, V _{Ds} =15V, I _D =20A		63	76	nC	
Total Gate Charge (4.5V)				33	40		
Gate Source Charge			Q _{gs}		8.6		
Gate Drain Charge			Q _{gd}		17.6		
Turn-On DelayTime	t _{d(on)}	V _{GS} =10V, V _{Ds} =15V, R _L =0.75Ω, R _{GEN} =3Ω		12		ns	
Turn-On Rise Time	t _r			15.5			
Turn-Off DelayTime	t _{d(off)}			40			
Turn-Off Fall Time	t _f			14			
Body Diode Reverse Recovery Time	t _{rr}	I _F = 20A, di/dt= 100A/μs		34	41	nA	
Body Diode Reverse Recovery Charge	Q _{rr}			30			
Maximum Body-Diode Continuous Current	I _S				4	A	
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V			1	V	

Note : The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

■ Marking

Marking	4444 KC****
---------	----------------

N-Channel MOSFET

AO4444 (KO4444)

■ Typical Characteristics




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

N-Channel MOSFET AO4444 (KO4444)

■ Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)




Figure 11: Normalized Maximum Transient Thermal Impedance