




## B560C

Advance

DIODE

### 5A SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER



#### DESCRIPTION


The UTC **B560C** is a schottky barrier rectifier; It provides the customers high efficiency and low power loss.

The UTC **B560C** is suitable for automatic assembly high frequency inverters and low voltage application, etc

#### FEATURES

- \* High efficiency
- \* Low power loss

#### SYMBOL



#### ORDERING INFORMATION

Ordering Number		Package	Pin Assignment		Packing
Lead Free	Halogen Free		1	2	
B560CL-SMC-R	B560CG-SMC-R	SMC	K	A	Tape Reel

Note: Pin Assignment: A: Anode, K: Cathode

<p>B560CL-SMC-R</p> <p>(1)Packing Type (2)Package Type (3)Lead Free</p>	<p>(1) R: Tape Reel (2) SMC: SMC (3) G: Halogen Free, L: Lead Free</p>
---	--

■ ABSOLUTE MAXIMUM RATINGS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Maximum Peak Repetitive Reverse Voltage	$V_{RRM}$	60	V
Maximum RMS Voltage	$V_{RMS}$	42	V
Maximum DC Blocking Voltage	$V_{DC}$	60	V
Average Rectified Output Current ( $T_T=90^{\circ}\text{C}$ )	$I_O$	5	A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed On Rated Load (JEDEC Method)	$I_{FSM}$	175	A
Operating Temperature	$T_J$	-55~+125	$^{\circ}\text{C}$
Storage Temperature	$T_{STG}$	-55~+150	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	$\theta_{JA}$	50	$^{\circ}\text{C}/\text{W}$

Note:  $8.0\text{mm}^2$  (0.13mm thick) land pads.

■ ELECTRICAL CHARACTERISTICS ( $T_A=25^{\circ}\text{C}$ , unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Forward Voltage $I_F=5\text{A}$ (Note 1)	$V_F$	0.70	V
DC Reverse Current at Rated DC	$I_R$	$T_A=25^{\circ}\text{C}$ 0.5	mA
Blocking Voltage (Note 1)		$T_A=100^{\circ}\text{C}$ 20	mA
Typical Total Capacitance (Note 2)	$C_T$	300	pF

Notes: 1. Pulse Test Pulse Width 300 $\mu\text{S}$ , Duty Cycle 2%.

2. Measured at 1.0MHz and applied reverse voltage of 4.0V.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.