


Small Signal Product
SOD-323 20~40V/1A Schottky Diode
FEATURES

- Low Forward Voltage Drop
- Surface mount device type
- Moisture sensitivity level 1
- Pb free and RoHS compliant


SOD-323

MECHANICAL DATA

- Case: Bend lead SOD-323 package
- High temperature soldering guaranteed: 260°C/10s
- Weight: 4.3mg (approximately)

APPLICATION

- General purpose rectification application

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)					
PARAMETER	SYMBOL	VALUE			UNIT
		B5817WS	B5818WS	B5819WS	
Non-Peak Repetitive Reverse Voltage	V _{RM}	20	30	40	V
Peak Repetitive Reverse Voltage	V _{RRM}	20	30	40	V
Working Peak Reverse Voltage	V _{RWM}	20	30	40	V
DC Blocking Voltage	V _R	20	30	40	V
RMS Reverse Voltage	V _{R(RMS)}	14	21	28	V
Average Rectified Output Current	I _O	1			A
Peak Forward Surge Current @t=8.3ms	I _{FSM}	9			A
Repetitive Peak Forward Current	I _{FRM}	1.5			A
Power Dissipation	P _D	250			mW
Thermal Resistance from Junction to Ambient	R _{thJA}	400			°C/W
Junction Temperature	T _J	125			°C
Storage Temperature Range	T _{STG}	- 55 to + 150			°C

PARAMETER	TEST CONDITION	SYMBOL	MIN	MAX	UNIT	
Reverse Breakdown Voltage	B5817WS	V _(BR)	20		V	
	B5818WS		at I _R = 1 mA	30		
	B5819WS			40		
Reverse Voltage Leakage Current	B5817WS	I _R		1	mA	
	B5818WS		at V _R = 20 V			--
	B5819WS		at V _R = 30 V			--
Forward Voltage	B5817WS	V _F	at I _F = 1A	0.45	V	
			at I _F = 3A	0.75		
	B5818WS		at I _F = 1A	0.55	V	
			at I _F = 3A	0.875		
	B5819WS		at I _F = 1A	0.6	V	
			at I _F = 3A	0.9		
Diode Capacitance	V _R =4V, f=1.0MHz	C _D	--	120	pF	

Small Signal Product

RATINGS AND CHARACTERISTICS CURVES

($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig. 1 Typical Forward Characteristics




Fig. 2 Typical Reverse Characteristics




Fig. 3 Typical Capacitance vs. VR





Fig. 4 Power Derating Curve



Small Signal Product


ORDERING INFORMATION						
PART NO.	MANUFACTURE CODE	PACKING CODE	GREEN COMPOUND CODE	PACKAGE	PACKING	MARKING
B5817WS	(Note)	RQ	G	SOD-323	3K / 7" Reel	SJ
B5818WS		RQ	G	SOD-323	3K / 7" Reel	SK
B5819WS		RQ	G	SOD-323	3K / 7" Reel	SL

Note: Indicator of manufacturing site for manufacture special control, if empty means no special control requirement

EXAMPLE					
PREFERRED P/N	PART NO.	MANUFACTURE CODE	PACKING CODE	GREEN COMPOUND CODE	DESCRIPTION
B5817WS RQG	B5817WS		RQ	G	Green compound
B5817WS-M0 RQG	B5817WS	M0	RQ	G	Green compound


Small Signal Product

**PACKAGE OUTLINE DIMENSIONS
SOD-323**



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	1.15	1.40	0.045	0.055
B	2.30	2.70	0.091	0.106
C	0.25	0.45	0.010	0.018
D	1.60	1.80	0.063	0.071
E	0.80	1.00	0.031	0.039
F	0.05	0.17	0.002	0.007
G	0.475 REF		0.19 REF	
H	-	0.10	-	0.004

SUGGESTED PAD LAYOUT



DIM.	Unit (mm)	Unit (inch)
	Typ.	Typ.
A	0.63	0.025
B	0.83	0.033
C	1.60	0.063
D	2.86	0.113

Small Signal Product**Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.