

**Micro Commercial Components** 



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

## Features

- Halogen free available upon request by adding suffix "-HF"
- Low Leakage Current
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Fast Switching For High Efficiency
- High emperature soldering guaranteed:260°C /10 seconds
- Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)

## **Maximum Ratings**

- Operating Temperature: -65°C to +125°C
- Storage Temperature: -65°C to +125°C
- Maximum Thermal Resistance; 25°C/W Junction To Lead


MCC Catalog Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
BA157	BA157	400V	280V	400V
BA158	BA158	600V	420V	600V
BA159	BA159	1000V	700V	1000V

### Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward	I <sub>F(AV)</sub>	1.0A	T <sub>A</sub> =50°C
Current Peak Forward Surge	I <sub>FSM</sub>	35A	8.3ms, half sine
Current	'FSM	00/1	0.0110, 1101 0110
Maximum			
Instantaneous	VF	1.3V	I <sub>FM</sub> = 1.0A;
Forward Voltage			T <sub>A</sub> = 25°C*
Maximum DC		<b>5</b> 0 <b>1</b>	T 0500
Reverse Current At	I <sub>R</sub>	5.0μΑ	T <sub>J</sub> = 25°C
Rated DC Blocking Voltage			
Maximum Reverse			
Recovery Time			
BA157~BA158	T <sub>rr</sub>	150nS	I <sub>F</sub> =0.5A,
BA159		250nS	I <sub>R</sub> =1.0A,
			I <sub>rr</sub> =0.25A
Typical Junction	CJ	15pF	Measured at
Capacitance			1.0MHz,
			V <sub>R</sub> =4.0V

BA157 THRU BA159

## 1 Amp Fast Recovery Rectifier 400~1000 Volts



\*Pulse test: Pulse width 300 μsec, Duty cycle 2% Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

www.mccsemi.com




SINGLE HALF

100

100

80

# **BA157 THRU BA159**



60

10

100

www.mccsemi.com

REVERSE VOLTAGE, VOLTS

**Revision:** B

2013/01/01



## **Ordering Information :**

Device	Packing	
Part Number-TP	Tape&Reel: 5Kpcs/Reel	
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box	
Part Number-BP	Bulk: 50Kpcs/Carton	

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# www.mccsemi.com