



BAS40TG

SURFACE MOUNT SCHOTTKY DIODES

VOLTAGE 40 Volts **CURRENT** 0.2 Amperes

SOD-723


Unit: inch (mm)

FEATURES

- Fast switching speed
- Surface mount package ideally suited for automatic insertion
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

- Case: SOD-723, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Appox Weight : 0.00077 gram



ABSOLUTE RATINGS (T_A=25°C , unless otherwise noted)

PARAMETER	Symbol	BAS40TG	Units
Marking	-	BD	-
Peak Reverse Voltage	V _{RRM}	40	V
Average Rectified Current at T _A =25°C	I _{F(AV)}	0.2	A
Non-repetitive Peak Forward Surge Current at t=1000m s	I _{FSM}	0.6	A
Power Dissipation	P _{TOT}	200	mW
Junction Temperature and Storage Temperature Rang	T _J , T _{STG}	-55 to 125	°C
Thermal Resistance , Junction to Ambient	R _{θJA}	635	°C/W







BAS40TG

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, unless otherwise noted)

PARAMETER	Symbol	Test Condition	MIN.	MAX.	Units
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R=10\mu\text{A}$	40	-	V
Reverse Current	I_R	$V_R=25\text{V}$	-	1.0	μA
Forward Voltage	V_F	$I_F=1\text{mA}$ $I_F=10\text{mA}$ $I_F=40\text{mA}$	-	0.38 0.5 1.0	V
Total Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$	-	5	pF


ELECTRICAL CHARACTERISTICS CURVE





BAS40TG

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 5K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2007

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.