



BC 485

BC 487


BC 489

NPN SILICON PLANAR EPITAXIAL TRANSISTORS

**MICRO ELECTRONICS**

BC485, BC487 and BC489 are NPN silicon planar epitaxial transistors designed for use as high voltage high current driver and output transistors.

CASE TO-92F



ABSOLUTE MAXIMUM RATINGS

		BC485	BC487	BC489
Collector-Base Voltage	VCBO	45V	60V	80V
Collector-Emitter Voltage	VCEO	45V	60V	80V
Emitter-Base Voltage	VEBO		5V	
Collector Current	IC		1A	
Total Power Dissipation @ TA=25°C	Ptot		625mW	
			1.5W	
Operating Junction & Storage Temperature	Tj, Tstg	-55 to +150°C		

ELECTRICAL CHARACTERISTICS AT TA=25°C

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	TEST CONDITIONS
Collector-Base Breakdown Voltage	BVCBO	↑			V	IC=0.1mA IE=0
Collector-Emitter Breakdown Voltage	BVCEO	Note 1			V	IC=10mA IB=0
Emitter-Base Breakdown Voltage	BVEBO	↓			V	IE=10µA IC=0
Collector Cutoff Current	ICBO			100	nA	VCB=VCBO IE=0
Collector-Emitter Saturation Voltage	VCE(SAT)*			0.5	V	IC=500mA IB=50mA
Base-Emitter Saturation Voltage	VBE(SAT)*			1.2	V	IC=500mA IB=50mA
D.C. Current Gain	HFE*	40				IC=10mA VCE=2V
		60		400		IC=100mA VCE=2V
		60		150		IC=100mA VCE=2V
		100		250		IC=100mA VCE=2V
		160		400		IC=100mA VCE=2V
		15				IC=1A VCE=5V
Current Gain-Bandwidth Product	fT		75		MHz	IC=50mA VCE=2V
Output Capacitance	Cob		12		pF	VCB=10V IE=0
Input Capacitance	Cib		85		pF	VBE=2V IC=0

Note 1 : equal to the values of the absolute maximum ratings.

\* Pulse Test : Pulse Width=0.3ms, Duty Cycle=1%

**MICRO ELECTRONICS LTD.**

38 HUNG TO ROAD, KWUN TONG, HONG KONG. TELEX 43510  
 KWUN TONG P. O. BOX69477 CABLE ADDRESS "MICROTRON"  
 TELEPHONE:- 3-430181-6 3-883363, 3-892423  
 FAX: 3-410321

7.79.8100A