



Micro Commercial Components™

Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

BC847AT, BT, CT

Features

- Epitaxial Die Construction
- Complementary PNP Type Available (BC857AT,BT,CT)
- Ultra-Small Surface Mount Package
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1

NPN
Surface Mount Small
Signal Transistor
150mW

Maximum Data

- Case: SOT-523
- Terminals: Solderable per MIL-STD-202, Method 208
- Polarity: See Diagram
- Marking:BC847AT--1E,BC847BT--1F,BC847CT-1G.

Maximum Ratings @ 25°C Unless Otherwise Specified


Symbol	Parameter	Value	Units
--------	-----------	-------	-------

OFF CHARACTERISTICS

$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	45	Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	50	Vdc
$V_{(BR)EBO}$	Collector-Emitter Breakdown Voltage	6.0	Vdc
I_C	Collector Current	100	mAdc
P_d	Power Dissipation (Note 1)	150	mW
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient(Note 1)	833	°C/W
T_J, T_{STG}	Operating & Storage Temperature	-55~+150	°C

Note: 1. Device mounted on FR-4 PCB with recommended pad layout

SOT-523



DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.059	.067	1.50	1.70	
B	.030	.033	0.75	0.85	
C	.057	.069	1.45	1.75	
D	.020 Nominal		0.50Nominal		
E	.035	.043	0.90	1.10	
G	.000	.004	.000	.100	
H	.028	.031	.70	0.80	
J	.004	.008	.100	.200	
K	.010	.014	.25	.35	

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units	Test Condition
OFF CHARACTERISTICS						
h_{FE}	DC Current Gain (Note 2)					$V_{CE}=5.0V, I_C=2.0mA$
	Current Gain A	110	---	222	---	
	B	200	290	450	---	
	C	420	520	800	---	
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage (Note 2)	---	---	250 600	mV	$I_C=10mA, I_B=0.5mA$ $I_C=100mA, I_B=5.0mA$
$V_{BE(SAT)}$	Base-Emitter Saturation Voltage (Note 2)	---	700 900	---	mV	$I_C=10mA, I_B=0.5mA$
$V_{BE(ON)}$	Base-Emitter Voltage (Note 2)	580 ---	660 ---	700 770	mV	$V_{CE}=5.0V, I_C=2.0mA$ $V_{CE}=5.0V, I_C=10mA$
I_{CBO} I_{CBO}	Collector-Cutoff Current (Note 2)	---	---	15	nA	$V_{CB}=30V, I_E=0$
		---	---	5.0	μA	$V_{CB}=30V, T_J=125^\circ C$
f_T	Gain Bandwidth Product	100	---	---	MHz	$V_{CE}=5.0V, I_C=10mA,$ $f=100MHz$
C_{CBO}	Collector-Base Capacitance	---	---	4.5	pF	$V_{CB}=10V, f=1.0MHz$
NF	Noise Figure	---	---	10	dB	$V_{CE}=5V, R_S=2.0Kohm,$ $f=1.0MHz, BW=200HZ$
		BC847BT	---	---		
BC847CT	---	---	---	---		

Note: 2. Short duration pulse test used to minimize self-heating effect.



Micro Commercial Components

Ordering Information

Device (Part Number)-TP	Packing Tape&Reel;3Kpcs/Reel
----------------------------	---------------------------------

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.