

SOUNDERS

- Industry compatible
- Competitively priced
- Sound output to 95dB

MECHANICAL BUZZERS



ORDERING INFORMATION

Ordering Code	Rated Voltage (V)	Operation Voltage (V)	Rated Current (mA)	Sound Output at 10cm (dB)	Resonate Frequency (Hz)	Tone	Operating Temp (°C)	Weight	Size
HJ50-110V/P	110	70.0 - 150.0	≤30	≥75	-	-	-25 ~ +110	20	30 x 23 x H8.5
FCE28-2S3120	12	9.0 - 15.0	≤40	≥95	2700 - 3200	Single	-20 ~ +70	10	ø28 x H20
FCE28-2P3120	12	8.0 - 15.0	≤15	≥85	2700 - 3200	Pulse	-20 ~ +70	10	ø28 x H20
CMB-06	6	3.0 - 8.0	≤23	≥82	300 - 500	-	-40 ~ +85	10	22.5 x 16.0 x H14.5
BMB-12	12	8.0 - 16.0	≤35	≥95	300 - 500	-	-40 ~ +70	17	26.0 x 26.0 x H19.7
NMB-06	6	4.0 - 8.0	≤35	≥95	300 - 500	-	-40 ~ +70	17	26.0 x 26.0 x H19.6

SOUNDERS

- Industry compatible
- Competitively priced
- Sound output to 95dB

DYNAMIC TRANSDUCERS



ORDERING INFORMATION

Ordering Code	Rated Imp (Ω)	Rate (Max) Power (W)	Sound Output at 10cm (dB) 1.5KHz	Resonate Frequency (kHz)	Rated Frequency Range (Hz)	Operating Temp (°C)	Weight	Size
XD41	8±15%	0.15 (0.2)	1000±20%	700 - 5000	≥81	-20 ~ +60	10	ø30 x H12.6
XD3108	8±20%	0.15 (0.2)	1100±150	700 - 4000	≥83	-20 ~ +60	11	ø31.7 x H15