


Silicon Controlled Rectifiers

PNPN devices designed for high volume, line-powered consumer applications such as relay and lamp drivers, small motor controls, gate drivers for larger thyristors, and sensing and detection circuits. Supplied in an inexpensive TO-226AA (TO-92) package which is readily adaptable for use in automatic insertion equipment.

- Sensitive Gate Trigger Current — 200 μ A Maximum
- Low Reverse and Forward Blocking Current — 100 μ A Maximum, $T_C = 125^\circ\text{C}$
- Low Holding Current — 5 mA Maximum
- Glass-Passivated Surface for Reliability and Uniformity

BRX44*
thru
BRX47*
BRX49*

SCRs
0.8 AMPERE RMS
30 TO 400 VOLTS



CASE 29-04
(TO-226AA)
STYLE 3
WITH TO-18 LEADFORM*

MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted.)

Rating	Symbol	Value	Unit	
Peak Repetitive Forward and Reverse Blocking Voltage ($T_J = 25$ to 125°C , $R_{GK} = 1000 \Omega$)	BRX44 BRX45 BRX46 BRX47 BRX49	V_{DRM} , V_{RRM}	30 60 100 200 400	Volts
Forward Current RMS (All Conduction Angles)	$I_T(\text{RMS})$	0.8	Amp	
Peak Forward Surge Current, $T_A = 25^\circ\text{C}$ (1/2 Cycle, Sine Wave, 60 Hz)	I_{TSM}	8	Amps	
Circuit Fusing Considerations, $T_A = 25^\circ\text{C}$ ($t = 8.3$ ms)	I^2t	0.15	A^2s	
Peak Gate Power — Forward, $T_A = 25^\circ\text{C}$	P_{GM}	0.1	Watt	
Peak Gate Current Forward, $T_A = 25^\circ\text{C}$ (300 μs , 120 PPS)	I_{GFM}	1	Amp	
Peak Gate Voltage — Reverse	V_{GRM}	5	Volts	
Operating Junction Temperature Range @ Rated V_{RRM} and V_{DRM}	T_J	-40 to +125	$^\circ\text{C}$	
Storage Temperature Range	T_{stg}	-40 to +150	$^\circ\text{C}$	
Lead Solder Temperature (< 1.5 mm from case, 10 s max.)		+230	$^\circ\text{C}$	

*European part numbers only . Package is Case 29 with Leadform 18.

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

BRX44 thru BRX47 BRX49

THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	75	$^{\circ}C/W$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	200	$^{\circ}C/W$

ELECTRICAL CHARACTERISTICS ($T_C = 25^{\circ}C$, $R_{GK} = 1000 \Omega$ unless otherwise noted.)


Characteristic	Symbol	Min	Max	Unit
Peak Forward Blocking Current ($V_D = \text{Rated } V_{DRM} @ T_C = 125^{\circ}C$)	I_{DRM}	—	100	μA
Peak Reverse Blocking Current ($V_R = \text{Rated } V_{RRM} @ T_C = 125^{\circ}C$)	I_{RRM}	—	100	μA
Forward "On" Voltage(1) ($I_{TM} = 1 \text{ A Peak } @ T_A = 25^{\circ}C$)	V_{TM}	—	1.7	Volts
Gate Trigger Current (Continuous dc)(2) (Anode Voltage = 7 Vdc, $R_L = 100 \text{ Ohms}$)	I_{GT}	—	200	μA
Gate Trigger Voltage (Continuous dc) (Anode Voltage = 7 Vdc, $R_L = 100 \text{ Ohms}$) (Anode Voltage = Rated V_{DRM} , $R_L = 100 \text{ Ohms}$)	V_{GT}	— — 0.1	0.8 1.2 —	Volts
Holding Current (Anode Voltage = 7 Vdc, initiating current = 20 mA)	I_H	— —	5 10	mA

- Forward current applied for 1 ms maximum duration, duty cycle $\leq 1\%$.
- R_{GK} current is not included in measurement.


**FIGURE 1 — CURRENT DERATING
(REFERENCE: CASE TEMPERATURE)**




**FIGURE 2 — CURRENT DERATING
(REFERENCE: AMBIENT TEMPERATURE)**



PACKAGE DIMENSIONS



STYLE 3:
 PIN 1. ANODE
 2. ANODE
 3. CATHODE



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. DIMENSION F APPLIES BETWEEN P AND L. DIMENSION D AND J APPLY BETWEEN L AND K. MINIMUM LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.022	0.41	0.55
F	0.016	0.019	0.41	0.48
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	—	12.70	—
L	0.250	—	6.35	—
N	0.080	0.105	2.04	2.66
P	—	0.100	—	2.54
R	0.115	—	2.93	—
V	0.135	—	3.43	—

CASE 029-04
 (TO-226AA)

BRX44 thru BRX47 BRX49

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters can and do vary in different applications. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and [®] are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Literature Distribution Centers:

USA: Motorola Literature Distribution; P.O. Box 20912; Phoenix, Arizona 85036.

EUROPE: Motorola Ltd.; European Literature Centre; 88 Tanners Drive, Blakelands, Milton Keynes, MK14 5BP, England.

JAPAN: Nippon Motorola Ltd.; 4-32-1, Nishi-Gotanda, Shinagawa-ku, Tokyo 141, Japan.

ASIA PACIFIC: Motorola Semiconductors H.K. Ltd.; Silicon Harbour Center, No. 2 Dai King Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong.



BRX44/D

