CMR3-02 CMR3-08 CMR3-04 CMR3-10 CMR3-06 CMR3-11

SURFACE MOUNT GENERAL PURPOSE SILICON RECTIFIER 3 AMP, 200 THRU 1100 VOLTS





www.centralsemi.com

#### **DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CMR3-02 Series 3.0 Amp Surface Mount Silicon Rectifier is a high quality, well constructed, highly reliable component designed for use in all types of commercial, industrial, entertainment, computer, and automotive applications. To order devices on 16mm Tape and Reel (3000/13" Reel), add TR13 suffix to part number.

# MARKING CODE: SEE MARKING CODE TABLE ON FOLLOWING PAGE

#### **FEATURES:**

- · Low cost
- Special selections available
- · High reliability
- Superior lot to lot consistency
- · Glass passivated chip
- "C" bend construction provides strain relief when mounted on pc board

## MAXIMUM RATINGS: (T<sub>A</sub>=25°C unless otherwise noted)

		CMR3	CMR3	CMR3	CMR3	CMR3	CMR3	
	SYMBOL	<u>-02</u>	<u>-04</u>	<u>-06</u>	<u>-08</u>	<u>-10</u>	<u>-11</u>	UNITS
Peak Repetitive Reverse Voltage	$V_{RRM}$	200	400	600	800	1000	1100	V
DC Blocking Voltage	$V_{R}$	200	400	600	800	1000	1100	V
RMS Reverse Voltage	V <sub>R</sub> (RMS)	140	280	420	560	700	770	V
Average Forward Current (T <sub>A</sub> =75°C)	lo			3	.0			Α
Peak Forward Surge Current, tp=8.3ms	I <sub>FSM</sub>			20	00			Α
Operating and Storage Junction Temperatur	e T <sub>J</sub> , T <sub>stg</sub>			-65 1	to +175			°C
Thermal Resistance	$\Theta_{\mathrm{JI}}$			1	0			°C/W

### **ELECTRICAL CHARACTERISTICS**: (T<sub>A</sub>=25°C unless otherwise noted)


SYMBOL	TEST CONDITIONS	MAX	UNITS
$I_{R}$	V <sub>R</sub> =Rated V <sub>RRM</sub>	5.0	μΑ
$I_{R}$	V <sub>R</sub> =Rated V <sub>RRM</sub> , T <sub>A</sub> =125°C	250	μΑ
$V_{F}$	I <sub>E</sub> =3.0A	1.2	V


CMR3-02 CMR3-08 CMR3-04 CMR3-10 CMR3-06 CMR3-11

SURFACE MOUNT GENERAL PURPOSE SILICON RECTIFIER 3 AMP, 200 THRU 1100 VOLTS



## **SMC CASE - MECHANICAL OUTLINE**





DEVICE	MARKING CODE		
CMR3-02	C302		
CMR3-04	C304		
CMR3-06	C306		
CMR3-08	C308		
CMR3-10	C310		
CMR3-11	C311		

DIMENSIONS						
	INC	HES	MILLIMETERS			
SYMBOL	MIN	MAX	MIN	MAX		
Α	0.030	0.060	0.76	1.52		
В	0.004	0.008	0.10	0.20		
С	0.305	0.320	7.75	8.13		
D	0.006	0.012	0.15	0.31		
Е	0.079	0.103	2.00	2.62		
F	0.260	0.280	6.60	7.11		
G	0.108	0.124	2.75	3.15		
Н	0.220	0.245	5.59	6.22		
OMO (DEV. DA)						

SMC (REV: R1)