

CNY75AX, CNY75BX, CNY75CX,  
CNY75A, CNY75B, CNY75C



# ISOCOM

COMPONENTS

## OPTICALLY COUPLED ISOLATOR PHOTOTRANSISTOR OUTPUT



### APPROVALS

- UL recognised, File No. E91231  
Package Code "GG"

### 'X' SPECIFICATION APPROVALS

- VDE 0884 in 3 available lead form : -  
- STD  
- G form  
- SMD approved to CECC 00802
- Certified to EN60950 by  
Nemko - Certificate No. P01102464

### DESCRIPTION


The CNY75A, CNY75B, CNY75C series of optically coupled isolators consist of infrared light emitting diode and NPN silicon photo transistor in a standard 6 pin dual in line plastic package.

### FEATURES

- Options :-  
10mm lead spread - add G after part no.  
Surface mount - add SM after part no.  
Tape & reel - add SMT & R after part no.
- High  $BV_{CEO}$  (90V min)
- High Isolation Voltage ( $5.3kV_{RMS}$ ,  $7.5kV_{PK}$ )
- All electrical parameters 100% tested
- Custom electrical selections available

### APPLICATIONS

- DC motor controllers
- Industrial systems controllers
- Measuring instruments
- Signal transmission between systems of different potentials and impedances



### ABSOLUTE MAXIMUM RATINGS (25°C unless otherwise specified)

Storage Temperature \_\_\_\_\_ -55°C to +150°C  
Operating Temperature \_\_\_\_\_ -55°C to +100°C  
Lead Soldering Temperature  
(1/16 inch (1.6mm) from case for 10 secs) 260°C

### INPUT DIODE


Forward Current \_\_\_\_\_ 60mA  
Reverse Voltage \_\_\_\_\_ 6V  
Power Dissipation \_\_\_\_\_ 105mW

### OUTPUT TRANSISTOR

Collector-emitter Voltage  $BV_{CEO}$  \_\_\_\_\_ 90V  
Collector-base Voltage  $BV_{CBO}$  \_\_\_\_\_ 90V  
Emitter-collector Voltage  $BV_{ECO}$  \_\_\_\_\_ 6V  
Collector Current \_\_\_\_\_ 50mA  
Power Dissipation \_\_\_\_\_ 160mW

### POWER DISSIPATION

Total Power Dissipation \_\_\_\_\_ 200mW  
(derate linearly 2.67mW/°C above 25°C)



**ISOCOM COMPONENTS LTD**  
Unit 25B, Park View Road West,  
Park View Industrial Estate, Brenda Road  
Hartlepool, TS25 1YD England Tel: (01429)863609  
Fax: (01429)863581 e-mail sales@isocom.co.uk  
<http://www.isocom.com>

**ELECTRICAL CHARACTERISTICS (  $T_A = 25^\circ\text{C}$  Unless otherwise noted )**


PARAMETER		MIN	TYP	MAX	UNITS	TEST CONDITION	
Input	Forward Voltage ( $V_F$ )		1.2	1.60	V	$I_F = 50\text{mA}$	
	Reverse Current ( $I_R$ )			10	$\mu\text{A}$	$V_R = 6\text{V}$	
Output	Collector-emitter Breakdown ( $BV_{CEO}$ ) ( Note 2 )	90			V	$I_C = 1\text{mA}$	
	Collector-base Breakdown ( $BV_{CBO}$ )	90			V	$I_C = 100\mu\text{A}$	
	Emitter-collector Breakdown ( $BV_{ECO}$ )	6			V	$I_E = 100\mu\text{A}$	
	Collector-emitter Dark Current ( $I_{CEO}$ )			150	nA	$V_{CE} = 20\text{V}$	
Coupled	$I_C / I_F$ (CTR) (Note 2)	CNY75A	15		%	$1\text{mA } I_F, 5\text{V } V_{CE}$	
		CNY75B	30		%	$1\text{mA } I_F, 5\text{V } V_{CE}$	
		CNY75C	60		%	$1\text{mA } I_F, 5\text{V } V_{CE}$	
		CNY75A	63	125	%	$10\text{mA } I_F, 5\text{V } V_{CE}$	
		CNY75B	100	200	%	$10\text{mA } I_F, 5\text{V } V_{CE}$	
		CNY75C	160	320	%	$10\text{mA } I_F, 5\text{V } V_{CE}$	
	Collector-emitter Saturation Voltage $V_{CE(SAT)}$			0.3	V	$10\text{mA } I_F, 1\text{mA } I_C$	
	Input to Output Isolation Voltage $V_{ISO}$		5300			$V_{RMS}$	See note 1
			7500			$V_{PK}$	See note 1
	Input-output Isolation Resistance $R_{ISO}$		$5 \times 10^{10}$			$\Omega$	$V_{IO} = 500\text{V}$ (note 1)

Note 1 Measured with input leads shorted together and output leads shorted together.


Note 2 Special Selections are available on request. Please consult the factory.

**TYPICAL SWITCHING CHARACTERISTICS**


Type	$R_L = 100\Omega$ see fig 1							$R_L = 1k\Omega$ see fig 2		
	td	tr	ton	ts	tf	toff	$I_C$	ton	toff	$I_F$
	$\mu\text{s}$	$\mu\text{s}$	$\mu\text{s}$	$\mu\text{s}$	$\mu\text{s}$	$\mu\text{s}$	mA	$\mu\text{s}$	$\mu\text{s}$	mA
CNY75A	2.0	2.5	4.5	0.3	2.7	3.0	10	10	25	20
CNY75B	2.5	3.0	5.5	0.3	3.7	4.0	10	16.5	20	10
CNY75C	2.8	4.2	7.0	0.3	4.7	5.0	10	11	37.5	10




**Collector Power Dissipation vs. Ambient Temperature**




**Collector Current vs. Collector-emitter Voltage (normalised to CNY75B)**




**Forward Current vs. Ambient Temperature**



**Current Transfer Ratio vs. Forward Current**



**Relative Current Transfer Ratio vs. Ambient Temperature**



**Collector-emitter Saturation Voltage vs. Ambient Temperature**

